

■ QUICK ASSEMBLY STRAIGHT PLUGS **SERIES 690**

MAIN TECHNICAL FEATURES:

- Straight industrial plugs according to the Standard EN 60309.
- In currents of 16 and 32 A.
- Protection degree IP44.
- Fast assembly without tools, screw terminals.
- Resistance to chemical or atmospheric agents.

CE

IP44

■ Quick assembly straight plugs - EN 60309 - In 16A - IP44

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC69470	■	2P	20-25 V~	without reference	10/80
EC69471	■	3P	20-25 V~	without reference	10/80
EC69170	■	2P+⊕	100-130 V~	4	10/80
EC69171	■	3P+⊕	100-130 V~	4	10/80
EC69070	■	2P+⊕	200-250 V~	6	10/80
EC69270	■	3P+⊕	200-250 V~	9	10/80
EC69271	■	3P+N+⊕	208-250 V~	9	10/80
EC69072	■	3P+⊕	380-415 V~	6	10/80
EC69074	■	3P+N+⊕	346-415 V~	6	10/80

■ Quick assembly straight plugs - EN 60309 - In 32A - IP44

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC69172	■	2P+⊕	100-130 V~	4	10/80
EC69173	■	3P+⊕	100-130 V~	4	10/80
EC69272	■	2P+⊕	200-250 V~	6	10/80
EC69273	■	3P+⊕	200-250 V~	9	10/80
EC69076	■	3P+⊕	380-415 V~	6	10/80
EC69078	■	3P+N+⊕	346-415 V~	6	10/60



EC69170



EC69070



EC69072

SYSTEMS ADAPTORS - MULTIPLIERS SERIES 690

MAIN TECHNICAL FEATURES:

- Systems adaptors domestic to industrial / industrial to domestic - IP20.
- 2-Way multipliers with plug EN 60309.
- Only for mobile and temporary use.
- Not usable in places with danger of explosion or fire.
- Always disconnect from the supply when not used.

CE

IP20

IP44

IP67

System adaptor industrial to domestic 10/16A 220/250 V~

IP20	ITEM	PLUG 16A	10/16A	SOCKETS 16A	PACKAGING PIECES
	EC690510	2P+⊕	2x 2P+⊕ Italian standard	1 Schuko/Italian standard	10/80
	EC690520	2P+⊕	2x 2P+⊕ Italian standard		10/90
	EC690525	2P+⊕		1 Schuko/Italian standard	10/90
	EC690530	3P+N+⊕		1 Schuko/Italian standard	10/90
	EC690540	3P+N+⊕	2x 2P+⊕ Italian standard		10/90

System adaptor domestic to industrial 16A 220/250 V~ IP20

ITEM	POLES	PLUG TYPE 16A	SOCKET 16A	PACKAGING PIECES
EC690512	2P+⊕	S31 Schuko	2P+⊕	10/80
EC690513	2P+⊕	S17 Italian	2P+⊕	10/80

2-Way multiplier and plug EN 60309 - In 16A - IP44

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC691702		2P+⊕	100-130 V~	4	10
EC690702		2P+⊕	200-250 V~	6	10
EC690722		3P+⊕	380-415 V~	6	10

2-Way multiplier and plug EN 60309 - In 16A - IP67

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC691742		2P+⊕	100-130 V~	4	5
EC690712		2P+⊕	200-250 V~	6	5
EC690732		3P+⊕	380-415 V~	6	5



EC690510



EC690520



EC690525



EC690512



EC690513



EC690712

MULTIPLIERS SERIE 690

MAIN TECHNICAL FEATURES:

- 3-Way multipliers with plug EN 60309.
- Only for mobile and temporary use.
- Not usable in places with danger of explosion or fire.
- To be always disconnected from the power when not used.

CE

IP44

IP67

3-Way multiplier and plug EN 60309 - In 16A - IP44

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC691703	Yellow	2P+⊕	100-130 V~	4	6
EC690703	Blue	2P+⊕	200-250 V~	6	5
EC692703	Blue	3P+⊕	200-250 V~	9	4
EC692713	Blue	3P+N+⊕	208-250 V~	9	4
EC690723	Red	3P+⊕	380-415 V~	6	4
EC690743	Red	3P+N+⊕	346-415 V~	6	4

3-Way multiplier and plug EN 60309 - In 32A - IP44

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC690763	Red	3P+⊕	380-415 V~	6	4
EC690783	Red	3P+N+⊕	346-415 V~	6	4

3-Way multiplier and plug EN 60309 - In 16A - IP67

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC691743	Yellow	2P+⊕	100-130 V~	4	6
EC690713	Blue	2P+⊕	200-250 V~	6	5
EC692743	Blue	3P+⊕	200-250 V~	9	4
EC692753	Blue	3P+N+⊕	208-250 V~	9	4
EC690733	Red	3P+⊕	380-415 V~	6	4
EC690753	Red	3P+N+⊕	346-415 V~	6	4

3-Way multiplier and plug EN 60309 - In 32A - IP67

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC690773	Red	3P+⊕	380-415 V~	6	4
EC690793	Red	3P+N+⊕	346-415 V~	6	4

3-Way multiplier with cable H07RN-F and plug EN 60309 - In 16A - IP67

ITEM	COLOUR	SOCKETS POLES	PLUG POLES	NOMINAL VOLTAGE	REFERENCE h PLUG / SOCKETS	CABLE	PACKAGING PIECES
EC690714-3	Blue / Blue	2P+⊕	2P+⊕	200-250 V~	6/6	3MT - 3G2,5	1
EC690714-20	Blue / Blue	2P+⊕	2P+⊕	200-250 V~	6/6	20MT - 3G2,5	1
EC690714-30	Blue / Blue	2P+⊕	2P+⊕	200-250 V~	6/6	30MT - 3G2,5	1
EC690754-3	Blue / Red	2P+⊕	3P+N+⊕	346-415 V~	6/6	3MT - 5G2,5	1



EC690703



EC690714-3



EC690754-3