

**EC69685**



**MOBILE SOCKET IP67 380V 3P+N+E 125A**

Industrial > Plugs and sockets > Portable > Sockets > Cee sockets (iec 60309) > Ip67 - 125 a



**Technical Symbols/Marks/Approvals**



**Norms**

EN 60309-1 EN 60309-2

**Etim**

**GROUP EG000014 - Industrial sockets/plug applications**

**CLASS EC001320 - CEE coupling (IEC 60309)**

|                                 |           |                                  |          |  |                         |
|---------------------------------|-----------|----------------------------------|----------|--|-------------------------|
| <b>Number of poles</b>          | 5         | <b>Degree of protection (IP)</b> | IP67     | <b>Material</b>                        | Plastic                 |
| <b>RAL-number</b>               | 7035      | <b>IEC-amperage</b>              | 125 A    | <b>Voltage according to EN 60309-2</b> | 400 V (50+60 Hz)<br>red |
| <b>Clock hour position</b>      | 6 h       | <b>Identification colour</b>     | Red      | <b>Connection system</b>               | Screwed terminal        |
| <b>Cable entry</b>              | Gland nut | <b>Insert direction</b>          | Straight | <b>Contact material</b>                | CuZn                    |
| <b>Surface coating contacts</b> | Untreated | <b>Military model</b>            | No       |  |                         |

**Documentation available for download**

**Certification**

IMQ\_CA02.05872\_2025\_125A.pdf

## Barcode



8033576779287

**Unit**

1 NR

1.3725 [kg]



8059307219259

**Pack**

2 NR

2.745 [kg]



8032793873426

**Cardboard**

8 NR

10.98 [kg]