

**EC400C1**



**JUNCTION BOX IP44 WITH STEPPED GLANDS DIM. 65X35**



Enclosures > Wall-mount > Wall-mount junction boxes > Series 400 - nipple version > Wall mount junction boxes > Ip44

**Technical Symbols/Marks/Approvals**



**Norms**

EN 60670-1 EN 60670-22

**Etim**

**GROUP EG000048 - Connection material (electrotechnical)**

**CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling**

<b>Rated insulation voltage Ui</b>	400 V	<b>Mounting method</b>	Wall-/ceiling mounting	<b>Degree of protection (IP)</b>	IP44
<b>Material</b>	Plastic	<b>Halogen free</b>	No	<b>Surface protection</b>	Untreated
<b>Colour</b>	Grey	<b>Width</b>	65 mm	<b>Depth</b>	35 mm
<b>Model</b>	Junction box	<b>Diameter</b>	65 mm	<b>Working temperature</b>	-25-70 °
<b>Explosion-tested version</b>	No	<b>For Ex-zone gas</b>	None	<b>For Ex-zone dust</b>	None
<b>Cover model</b>	Blind cover	<b>Circuit integrity</b>	None	<b>Equipped with</b>	None
<b>Shape</b>	Round	<b>Number of inlets</b>	4	<b>Inlet from the rear</b>	No
<b>Transparent cover</b>	No	<b>Connectable</b>	No	<b>For tube diameter</b>	20 mm
<b>Mounting in the soil</b>	No	<b>Mounting under water</b>	No	<b>Type of housing feed-through</b>	Trimnable step membrane
<b>Cover attachment</b>	Snapped on	<b>Castable</b>	No	<b>Casting compound included</b>	No
<b>Sealable</b>	No	<b>With screening</b>	No	<b>Weatherproof</b>	Yes

**Documentation available for download**



## Barcode



8054320283768

**Pack**

5 NR

0.25 [kg]



8057711599707

**Cardboard**

120 NR

0.39x0.295x0.3 [m]

6 [kg]