

EC420C6



**SMOOTH SIDED BOX IP56 WITH
TRANSPARENT LID DIM. 190X140X70**

Enclosures > Wall-mount > Wall-mount junction boxes > Series 420 - smooth sides - transparent cover lid > Wall mount junction boxes



Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

| | | | | | |
|-------------------------------------|--------------|---------------------------------|------------------------|----------------------------------|-----------|
| Rated insulation voltage Ui | 400 V | Mounting method | Wall-/ceiling mounting | Degree of protection (IP) | IP56 |
| Material | Plastic | Halogen free | Yes | Surface protection | Untreated |
| Colour | Grey | Width | 190 mm | Depth | 70 mm |
| Model | Junction box | Length | 140 mm | Diameter | 0 mm |
| Working temperature | -25-70 °C | Explosion-tested version | No | For Ex-zone gas | None |
| For Ex-zone dust | None | Cover model | Blind cover | Circuit integrity | None |
| Equipped with | None | Shape | Rectangular | Number of inlets | 0 |
| Inlet from the rear | No | Transparent cover | Yes | Connectable | No |
| For tube diameter | Other | Mounting in the soil | No | Mounting under water | No |
| Type of housing feed-through | None | Cover attachment | Screwed | Castable | Yes |
| Casting compound included | No | Sealable | No | With screening | No |
| Weatherproof | Yes | | | | |

Documentation available for download

Certification

Serie 400 IP56
IMQ_EI884_2018.pdf

Barcode



8032636761538

Unit

1 NR

0.375 [kg]



8057711599899

Cardboard

24 NR

0.605x0.4x0.35 [m]

9 [kg]