

ECTC1250



**PLIABLE PVC CONDUIT 22212 Ø50 mm
- 25 m**

Conduits and fittings > Conduits > Corrugated conduits > Series tc12 - pvc - class 22212 - 320 n > plastic conduits > Light grey




IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-22

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7035	UV resistant	No
Suitable for underground installation	No	Operating temperature	-5-60 °C	Bending strength	Pliable
Compressive strength class according to EN 61386-1	Light (class 2 / 1 Joule)	Impact strength class according to EN 61386-1	Light (class 2 / 1 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	No	Suitable for installation on wood	No
Suitable for hollow wall installation	No	Suitable for concrete installation	Yes	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	40.4 mm
Outer diameter	50 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download

Certification

 OVE_50017-001-09.pdf

Certification

 OVE_50017-001-10.pdf

Barcode



8054320285816

Cardboard

25 MT

0.6x0.6x0.22 [m]

4.245 [kg]



BAHAGTC1250

Pallet

800 MT

0.8x1.2x2.5 [m]

135.84 [kg]