

ECTP1225T

HF PLAIBLE CONDUIT 22323 Ø25 mm - 50 m WITH DRAW TAPE - ORANGE



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Conduits and fittings > Conduits > Corrugated conduits >
Series tp12 - pp - class 22323 - 320 n > plastic conduits >
Orange - cable puller

Technical Symbols/Marks/Approvals

HF

+90°



RoHS II

MADE
IN
ITALY

Norms

EN 61386-1 EN 61386-22 EN 61034-2 EN 50642

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polypropylene (PP)	Halogen free	Yes
Colour	Orange	RAL-number	2004	UV resistant	No
Suitable for underground installation	No	Operating temperature	-15-90 °C	Bending strength	Pliable, self recovering
Compressive strength class according to EN 61386-1	Light (class 2 / 1 Joule)	Impact strength class according to EN 61386-1	Light (class 2 / 1 Joule)	With sleeve	No
Fire retardant version	No	Surface mounting	No	Suitable for installation on wood	No
Suitable for hollow wall installation	No	Suitable for concrete installation	No	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	18.6 mm
Outer diameter	25 mm	High conducting inner coating	Yes	With metre indication	No

Barcode



8054320281924

Cardboard

50 MT

0.55x0.55x0.2 [m]

3.35 [kg]



8054320282228

Pallet

3000 MT

0.8x1.2x2.5 [m]

201 [kg]