

**ECGFE35N**



**FLEXIBLE SPIRAL CONDUIT 23114 Ø35 mm - 30 m - BLACK**

Conduits and fittings > Spiral conduits > Flexible spiral conduits > Series gfe - class 23114 - 750n > Spiral flexible conduits > Black



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**



**Norms**

EN 61386-1 EN 61386-23 UL 1696

**Etim**

**GROUP EG000003 - Protective hose systems**

**CLASS EC001177 - Protective plastic hose**

<b>Material</b>	Polyvinyl chloride (PVC)	<b>Halogen free</b>	No	<b>Colour</b>	Black
<b>UV resistant</b>	Yes	<b>Working temperature</b>	5-60 °C	<b>Nominal diameter</b>	35 mm
<b>Inner diameter</b>	35 mm	<b>Outer diameter</b>	41 mm	<b>Compressive strength</b>	320 N
<b>Bending radius, static</b>	350 mm	<b>Tensile strength</b>	100 N	<b>Approved according to DIN EN 61386-23</b>	Yes
<b>Approved according to UR</b>	Yes	<b>Approved according to CSA</b>	No	<b>Material filament</b>	Helix of rigid plastic
<b>Plain interior</b>	Yes	<b>Plain exterior</b>	No	<b>Flexibility</b>	Flexible
<b>Approved according to N</b>	No				

**Documentation available for download**

**Certification**

Certificato UL  
GUAINA E173313-  
2021.pdf

## Barcode



8050880888580

**Cardboard**

30 MT

0.61x0.61x0.19 [m]

8.001 [kg]



8057711593903

**Pallet**

1440 MT

384.048 [kg]