

ECGFE20N

FLEXIBLE SPIRAL CONDUIT 23114 Ø20 mm - 30 m - BLACK



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Conduits and fittings > Spiral conduits > Flexible spiral conduits > Series gfe - class 23114 - 750n > Spiral flexible conduits > Black

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-23 UL 1696

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001177 - Protective plastic hose

| | | | | | |
|---------------------------------|--------------------------|----------------------------------|---------|--|------------------------|
| Material | Polyvinyl chloride (PVC) | Halogen free | No | Colour | Black |
| UV resistant | Yes | Working temperature | 5-60 °C | Nominal diameter | 16 mm |
| Inner diameter | 20 mm | Outer diameter | 24.7 mm | Compressive strength | 320 N |
| Bending radius, static | 200 mm | Tensile strength | 100 N | Approved according to DIN EN 61386-23 | Yes |
| Approved according to UR | Yes | Approved according to CSA | No | Material filament | Helix of rigid plastic |
| Plain interior | Yes | Plain exterior | No | Flexibility | Flexible |
| Approved according to N | No | | | | |

Documentation available for download

Certification
Certificato UL
GUAINE E173313-
2021.pdf

Certification
Serie Guaine e
raccordi
IMQ_CA02.06109_
2023.pdf

Barcode



8050880888511

Cardboard

30 MT

0.48x0.48x0.11 [m]

3.801 [kg]



8057711593835

Pallet

4320 MT

547.344 [kg]