

**ECMC2020B**



**MINITRUNKING FRONT-HOOKING LID  
20X20 WHITE 1 COMPARTMENT**

Trunkings > Wall and ceiling > Miniature solid trunkings > Series mc - front lid > Mini/maxi trunkings > White



**Technical Symbols/Marks/Approvals**

|                      |             |                    |                     |           |                |  |  |
|----------------------|-------------|--------------------|---------------------|-----------|----------------|--|--|
| <b>IK07</b>          | <b>IP40</b> | <b>UL94<br/>V0</b> | <b>GWT<br/>960°</b> | <b>CE</b> | <b>RoHS II</b> |  |  |
| <b>MADE IN ITALY</b> |             |                    |                     |           |                |  |  |

**Norms**

EN 50085-1 EN 50085-2-1

**Description**

Mini-trunking made of self-extinguishing rigid PVC technopolymer. The bottom is pre-drilled for fastening with screws and anchors. The bottom is designed for quick fastening with silicone adhesives. The front-hinged lid is supplied assembled.

**Etim**

**GROUP EG000006 - Installation ducts for wall and ceiling**

**CLASS EC000059 - Mini/maxi trunking**

|                                       |                    |                                       |                     |                                     |                          |
|---------------------------------------|--------------------|---------------------------------------|---------------------|-------------------------------------|--------------------------|
| <b>Degree of protection (IP)</b>      | IP40               | <b>Material</b>                       | Plastic             | <b>Material quality</b>             | Polyvinyl chloride (PVC) |
| <b>Halogen free</b>                   | No                 | <b>Anti-bacterial treatment</b>       | No                  | <b>Surface protection</b>           | Untreated                |
| <b>Colour</b>                         | White              | <b>Transparent</b>                    | No                  | <b>Impact strength</b>              | IK07                     |
| <b>Type of fastening</b>              | Bottom perforation | <b>Width</b>                          | 20 mm               | <b>Height</b>                       | 20 mm                    |
| <b>Length</b>                         | 2 m                | <b>Usable cross section</b>           | 264 mm <sup>2</sup> | <b>RAL-number</b>                   | 9001                     |
| <b>With protective foil</b>           | No                 | <b>Working temperature</b>            | -5-60 °C            | <b>Cover model</b>                  | Loose                    |
| <b>Suitable for circuit integrity</b> | No                 | <b>Number of permanent partitions</b> | 0                   | <b>Number of plug-in partitions</b> | 0                        |
| <b>With cable fixing clip</b>         | No                 | <b>With duct connector</b>            | No                  | <b>Delivery on roll</b>             | No                       |
| <b>Pre-stamping</b>                   | No                 |                                       |                     |                                     |                          |

## Documentation available for download



## Barcode



8054320287629

**Cardboard**

90 MT

0.195x0.102x2.025 [m]

10.998 [kg]