

EC625006



**GRP POLYESTER ENCLOSURE SOLID
DOOR 140 MODULES (5X28)
620X810X320 mm**



Enclosures > Wall-mount > Grp enclosures > Boards > Distribution board > Blank door

Technical Symbols/Marks/Approvals

IP66	GWT 960°	UL94 V0	UV	IK10	HF		CE
RoHS II		MADE IN ITALY					

Norms

EN 62208

Etim

**GROUP EG000011 - Enclosures/cabinets
CLASS EC000261 - Enclosure/cabinet (empty)**

Degree of protection (IP)	IP66	Material	Other	Material quality	GRP (Glass fibre reinforced plastic)
Surface finishing	Untreated	Colour	Grey	Impact strength	IK10
Width	620 mm	Height	810 mm	Depth	320 mm
With cover	Yes	RAL-number	7035	With mounting plate	No
Pre-stamping	No	EMC-version	No	Suitable for wall mounting	Yes
Couplable	Yes	Mounting plate depth-adjustable	Yes	Suitable for wall built-in	No
Pole fastening	Yes	With door	Yes	Number of doors	1
With glazed door	No	With ventilation door	No	With rear door	No
Number of locks	2	Transparent cover	No	Suitable for outdoor set-up	Yes
Pitched roof	No	Number of connector holes	0	Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890	96 W
Max. permitted load of the mounting plate according to IEC 62208	80 kg				

Documentation available for download

Instruction booklet
Istruzioni_625_042
3.pdf

Certification
MI22-0079305-01a
- ELETTROCANALI
SPA - HCI_1 -
TR_625.pdf

Certification
MI22-0079305-01b
- ELETTROCANALI
SPA - pH -
TR_625.pdf

Certification
MI22-0079305-01c
- ELETTROCANALI
SPA - HCI_3 -
TR_625.pdf

Certification
MI22-0079343-
01_TR_625.pdf

Certification
Serie 625
IMQ_CA02.06897_
2024.pdf

Brochure
Quadri Poliestere
IT.pdf

Brochure
Quadri
Poliestere_ENG.pdf

Barcode



8053676570393
Unit
1 NR
13.9 [kg]