

EC625013



GRP POLYESTER ENCLOSURE TRANSPARENT DOOR 54 MODULES (3X18) 435X505X215 mm

Enclosures > Wall-mount > Grp enclosures > Boards >
Distribution board > Transparent window door



Technical Symbols/Marks/Approvals

IP66	GWT 960°	UL94 V0	UV	IK10	HF		CE
RoHS II		MADE IN ITALY					

Norms

EN 62208

Etim

GROUP EG000011 - Enclosures/cabinets

CLASS EC000261 - Enclosure/cabinet (empty)

Degree of protection (IP)	IP66	Material	Other	Material quality	GRP (Glass fibre reinforced plastic)
Surface finishing	Untreated	Colour	Grey	Impact strength	IK10
Width	435 mm	Height	505 mm	Depth	215 mm
With cover	Yes	RAL-number	7035	With mounting plate	No
Pre-stamping	No	EMC-version	No	Suitable for wall mounting	Yes
Couplable	Yes	Mounting plate depth-adjustable	Yes	Suitable for wall built-in	No
Pole fastening	Yes	With door	Yes	Number of doors	1
With glazed door	Yes	With ventilation door	No	With rear door	No
Number of locks	2	Transparent cover	No	Suitable for outdoor set-up	Yes
Pitched roof	No	Number of connector holes	0	Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890	53 W
Max. permitted load of the mounting plate according to IEC 62208	35 kg				

Documentation available for download

 Instruction booklet Istruzioni_625_0423.pdf	 Certification MI22-0079305-01a - ELETTRICANALI SPA - HCI_1 - TR_625.pdf	 Certification MI22-0079305-01b - ELETTRICANALI SPA - pH - TR_625.pdf
 Certification MI22-0079305-01c - ELETTRICANALI SPA - HCI_3 - TR_625.pdf	 Certification MI22-0079343- 01_TR_625.pdf	 Certification Serie 625 IMQ_CA02.06897_ 2024.pdf
 Brochure Quadri Poliestere IT.pdf	 Brochure Quadri Poliestere_ENG.pdf	

Barcode



8053676570430

Unit

1 NR

6.4 [kg]