

# Specifications

## Eaton 262678

Eaton Moeller series xPole - PL7 MCB.  
Miniature circuit breaker (MCB), 25 A, 1p,  
characteristic: B

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series xPole - PL7 MCB
<b>CATALOG NUMBER</b>	262678
<b>EAN</b>	4015082626785
<b>PRODUCT LENGTH/DEPTH</b>	71 mm
<b>PRODUCT HEIGHT</b>	82 mm
<b>PRODUCT WIDTH</b>	17.6 mm
<b>PRODUCT WEIGHT</b>	0.12 kg
<b>COMPLIANCES</b>	RoHS conform
<b>MODEL CODE</b>	PL7-B25/1



*Powering Business Worldwide*

## Delivery program

<b>APPLICATION</b>	<ul style="list-style-type: none"><li>• Switchgear for residential and commercial applications</li><li>• xPole - Switchgear for residential and commercial applications</li></ul>
--------------------	---

<b>NUMBER OF POLES</b>	Single-pole
<b>NUMBER OF POLES (TOTAL)</b>	1
<b>NUMBER OF POLES (PROTECTED)</b>	1
<b>TRIPPING CHARACTERISTIC</b>	B
<b>RELEASE CHARACTERISTIC</b>	B
<b>AMPERAGE RATING</b>	25 A

<b>TYPE</b>	<ul style="list-style-type: none"><li>• Miniature circuit breaker</li><li>• PL7</li></ul>
-------------	---

## Technical data - electrical

<b>VOLTAGE TYPE</b>	AC
<b>RATED OPERATIONAL VOLTAGE (UE) - MAX</b>	230 V
<b>RATED INSULATION VOLTAGE (UI)</b>	440 V
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	4 kV
<b>FREQUENCY RATING - MIN</b>	50 Hz
<b>FREQUENCY RATING - MAX</b>	60 Hz
<b>RATED SWITCHING CAPACITY (IEC/EN 60898-1)</b>	10 kA
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 230 V</b>	10 kA
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 400 V</b>	10 kA
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 230 V</b>	0 kA
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 400 V</b>	0 kA
<b>OVERVOLTAGE CATEGORY</b>	III
<b>POLLUTION DEGREE</b>	2

## Technical data - mechanical

<b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>	1
--	---

<b>BUILT-IN DEPTH</b>	70.5 mm
-----------------------	---------

<b>DEGREE OF PROTECTION</b>	IP20
-----------------------------	------

<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN</b>	1 mm <sup>2</sup>
---	-------------------

<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX</b>	25 mm <sup>2</sup>
---	--------------------

<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN</b>	1 mm <sup>2</sup>
--	-------------------

<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX</b>	25 mm <sup>2</sup>
--	--------------------

## Design verification as per IEC/EN 61439 - technical data

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	25 A
--	------

<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT</b>	0 W
---	-----

<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>	3 W
--	-----

<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT</b>	0 W
---	-----

<b>HEAT DISSIPATION CAPACITY</b>	0 W
----------------------------------	-----

<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
--	--------

<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	75 °C
--	-------

## Design verification as per IEC/EN 61439

<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF</b>	Is the panel builder's responsibility.

## Additional information

<b>CURRENT LIMITING CLASS</b>	3
<b>FEATURES</b>	Additional equipment possible
<b>SPECIAL FEATURES</b>	Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
<b>USED WITH</b>	PL7 Miniature circuit breaker

---

**INSULATING MATERIAL**

---

**10.10 TEMPERATURE RISE**

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

**10.11 SHORT-CIRCUIT RATING**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.12 ELECTROMAGNETIC COMPATIBILITY**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL FUNCTION**

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

---

## Resources

CATALOGUES	<a href="#">eaton-xpole-accessories-ca019015en-en-us.pdf</a>
	<a href="#">eaton-xpole-pl7-mcb-catalog-ca019068en-en-us.pdf</a>
	<a href="#">eaton-xpole-protective-devices-catalog-ca019014en-en-us.pdf</a>
CHARACTERISTIC CURVE	<a href="#">eaton-xpole-mmc4-6-m-mcb-characteristic-curve.jpg</a>
DECLARATIONS OF CONFORMITY	<a href="#">DA-DC-03_PL7</a>
DRAWINGS	<a href="#">eaton-xpole-mmc4-6-m-mcb-dimensions.jpg</a>
	<a href="#">eaton-xpole-mmc4-6-m-mcb-3d-drawing-006.jpg</a>
INSTALLATION INSTRUCTIONS	<a href="#">eaton-rccb-rcbo-g9-il019140zu.pdf</a>
MCAD MODEL	<a href="#">pls_1p.dwg</a> <a href="#">pls_1p.stp</a>
PEP ECO-PASSPORT	<a href="#">EATO-00046-V01.01-EN</a>
WIRING DIAGRAMS	<a href="#">eaton-xpole-mmc4-6-m-mcb-wiring-diagram-002.jpg</a>

---

PROJECT NAME:

---

PROJECT NUMBER:

---

PREPARED BY:

---

DATE:

---



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

