

ECTG1550



RIGID CONDUIT 33211 Ø50 mm - 3 m - BUNDLE 15

Conduits and fittings > Conduits > Rigid conduits > Series tg15
- pvc - class 33211 - 750 n > plastic conduits > 3 meters -
length



IMMAGINE RAPPRESENTATIVA **EC** REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21

Etim

GROUP EG000002 - Pipes/hoses for cable installation


CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7035	UV resistant	Yes
Suitable for underground installation	Yes	Operating temperature	-5-60 °C	Bending strength	Rigid
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	Yes	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	No	Machine and systems installation	Yes
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	Yes	Inner diameter	45.3 mm
Outer diameter	50 mm	High conducting inner coating	No	With metre indication	No


Documentation available for download



Certification
Tubo Rigido TG15
e
Raccordi_2023.pdf




Certification
Tubo rigido
IMQ_EN835_2023-
01-12.pdf




Certification
LICENCE NF -
TG15 -2022 -
Licence - Certificat
Produits-14694838-
778138-
0000732340-
6.p....pdf

Barcode



8054320284680
Cardboard
15 MT
6.3255 [kg]



barcode
8057711598939
Pallet
360 MT
3x0.61x0.63 [m]
151.812 [kg]