

**ECTG1250B**



**RIGID CONDUIT 22211 Ø50 mm - 3 m - BELL END**



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Conduits and fittings > Conduits > Rigid conduits > Series tg12  
- pvc - class 22211 - 320 n > plastic conduits > 3 meters -  
length - bell end

**Technical Symbols/Marks/Approvals**



**Norms**

EN 61386-1 EN 61386-21

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC001174 - Plastic installation tube**

<b>Flush-mounted installation</b>	Yes	<b>Material</b>	Polyvinyl chloride (PVC)	<b>Halogen free</b>	No
<b>Colour</b>	Grey	<b>RAL-number</b>	7035	<b>UV resistant</b>	Yes
<b>Suitable for underground installation</b>	No	<b>Operating temperature</b>	-5-60 °C	<b>Bending strength</b>	Rigid
<b>Compressive strength class according to EN 61386-1</b>	Light (class 2 / 1 Joule)	<b>Impact strength class according to EN 61386-1</b>	Light (class 2 / 1 Joule)	<b>With sleeve</b>	Yes
<b>Fire retardant version</b>	Yes	<b>Surface mounting</b>	Yes	<b>Suitable for installation on wood</b>	Yes
<b>Suitable for hollow wall installation</b>	Yes	<b>Suitable for concrete installation</b>	No	<b>Machine and systems installation</b>	No
<b>Suitable for underfloor installation (screed)</b>	No	<b>Suitable for outdoor installation</b>	No	<b>Inner diameter</b>	46.4 mm
<b>Outer diameter</b>	50 mm	<b>High conducting inner coating</b>	No	<b>With metre indication</b>	No

**Documentation available for download**

**Certification**  
**OVE\_50017-003-09.pdf**

**Certification**  
**OVE\_50017-003-10.pdf**

## Barcode



8054320284901

**Cardboard**

15 MT

5.6205 [kg]



8057711598717

**Pallet**

360 MT

134.892 [kg]