

**EC51021**

**CABLE GLAND THREAD PG 21 GREY WITH LOCK NUT**



Enclosures > Accessories > Accessories > Cable glands > Cable gland > Pg pitch - grey - with lock nut

**Technical Symbols/Marks/Approvals**

IP68	GWT 650°	CE	RoHS II	MADE IN ITALY
------	----------	----	---------	---------------

**Norms**

DIN 40430

**Etim**

**GROUP EG000009 - Cable and wire entry systems**

**CLASS EC000441 - Cable gland**

<b>Degree of protection (IP)</b>	IP68	<b>Material</b>	Plastic	<b>Material quality</b>	Polyamide (PA)
<b>Halogen free</b>	Yes	<b>Surface protection</b>	Untreated	<b>Colour</b>	Grey
<b>Model</b>	Straight	<b>RAL-number</b>	7035	<b>With strain relief</b>	No
<b>Working temperature</b>	-30-90 °C	<b>Thread type</b>	PG	<b>Nominal thread size metric/PG</b>	21
<b>Pitch thread</b>	1.588 mm	<b>Glass-fibre reinforced</b>	No	<b>Shock resistant</b>	Yes
<b>Explosion-tested version</b>	No	<b>For Ex-zone gas</b>	None	<b>For Ex-zone dust</b>	None
<b>Pressure-compensating</b>	No	<b>EMC-version</b>	No	<b>Thread length</b>	10.7 mm
<b>Wrench width</b>	33 mm	<b>Hexagon angular dimension</b>	60 °	<b>Suitable for cable diameter</b>	13-18 mm
<b>Bend radius protection/trumpet flare</b>	No	<b>With locknut</b>	Yes	<b>Snapping in opening</b>	No
<b>Multi seal area</b>	No	<b>Flat cable coupling</b>	No	<b>Type of sealing</b>	Sealing ring
<b>Separable screw gland</b>	No	<b>For armoured cable</b>	No	<b>Screened</b>	No

**Technical Characteristics**

**Mounting hole diameter** 29 mm

## Barcode



8050880881949

**Pack**

50 NR

1.165 [kg]



8057711590391

**Cardboard**

300 NR

0.39x0.295x0.21 [m]

6.99 [kg]