


## EC660633M

### SCHUNTING SWITCHES 63A - 3P - 205X155X125



Industrial > Safety rotary switches > Safety switches > Control  
version > Switch disconnecter (low voltage) > Disconnectors 16  
a ÷ 100 a

#### Technical Symbols/Marks/Approvals



#### Norms

IEC947-3 EN60947-3 UL508

**Etim**


**GROUP EG000017 - Low-voltage switchgear and control gear**  
**CLASS EC000216 - Switch disconnecter (low voltage)**

<b>Number of poles</b>	3	<b>Width</b>	155 mm	<b>Height</b>	205 mm
<b>Depth</b>	125 mm	<b>Version as main switch</b>	No	<b>Version as maintenance-/service switch</b>	Yes
<b>Version as safety switch</b>	No	<b>Version as emergency stop installation</b>	No	<b>Version as reversing switch</b>	No
<b>Number of switches</b>	1	<b>Max. rated operation voltage Ue AC</b>	690 V	<b>Rated operating voltage</b>	230-690 V
<b>Rated permanent current Iu</b>	63 A	<b>Rated permanent current at AC-23, 400 V</b>	50 A	<b>Rated permanent current at AC-21, 400 V</b>	63 A
<b>Rated operation power at AC-3, 400 V</b>	22 kW	<b>Rated short-time withstand current Icw</b>	1500 A	<b>Rated operation power at AC-23, 400 V</b>	30 kW
<b>Switching power at 400 V</b>	30 kW	<b>Conditioned rated short-circuit current Iq</b>	10 kA	<b>Number of auxiliary contacts as normally closed contact</b>	0
<b>Number of auxiliary contacts as normally open contact</b>	0	<b>Number of auxiliary contacts as change-over contact</b>	0	<b>Motor drive optional</b>	No
<b>Motor drive integrated</b>	No	<b>Voltage release optional</b>	No	<b>Device construction</b>	Complete device in housing
<b>Suitable for floor mounting</b>	No	<b>Suitable for front mounting 4-hole</b>	Yes	<b>Suitable for front mounting centre</b>	No
<b>Suitable for distribution board installation</b>	No	<b>Suitable for intermediate mounting</b>	No	<b>Colour control element</b>	Black
<b>Type of control element</b>	Turn button	<b>Interlockable</b>	Yes	<b>Type of electrical connection of main circuit</b>	Cable clamp
<b>With pre-assembled cabling</b>	No	<b>Degree of protection (IP), front side</b>	IP67		

**Technical Characteristics**

dimensions 205x155x125 mm

**Barcode**



8053676575695  
**Unit**  
1 NR  
0.2x0.154x0.145 [m]  
0.935 [kg]



8059307215374  
**Cardboard**  
10 NR  
0.605x0.4x0.35 [m]  
9.35 [kg]