



Data

## Electrical data

### Ratings per IEC/EN 60664-1

Rated voltage (II / 2)	400 V
Rated impulse voltage (II / 2)	4 kV
Rated current	24 A
Legend (ratings)	(II / 2) $\Delta$ Overvoltage category II / Pollution degree 2

## Connection data

Connection technology	CAGE CLAMP®
Actuation type	Push-in
Connectable conductor materials	Copper
Solid conductor	0.5 ... 2.5 mm <sup>2</sup> / 20 ... 16 AWG
Fine-stranded conductor	0.5 ... 2.5 mm <sup>2</sup> / 20 ... 16 AWG
Strip length	9 ... 11 mm / 0.35 ... 0.43 Inch
Total number of connection points	2
Total number of potentials	1
Type of wiring	Side-entry wiring

## Geometrical Data

Width	8 mm / 0.315 inch
Height	15.5 mm / 0.61 inch
Depth	42 mm / 1.654 inch

## Material Data

Color	gray
Fire load	0.099 MJ
Weight	5 g

## Commercial data

Country of origin	CH
GTIN	4044918818407
Customs Tariff No.	85369010000

## Approvals / Certificates

### Country specific Approvals

Logo	Approval	Certificate name
	CSA DEKRA Certification B.V.	1053495