



## General info

### Indoor - Suspensions

Indoor suspended lamp with integrated LED sources and direct light emission

|                     |  |
|---------------------|--|
| <b>Ean</b>          | 8021696259178                              |
| <b>Item</b>         | ORACLE SLIM SP D070 SQUARE 3000K ON-OFF WH |
| <b>Installation</b> | Suspension                                 |
| <b>Guarantee</b>    | 5 years                                    |
| <b>Gross weight</b> | 3.49 kg                                    |
| <b>Volume</b>       | 0.081928 m <sup>3</sup>                    |

## Technical info

|                              |  |
|------------------------------|--|
| <b>Net weight</b>            | 2 kg   |
| <b>Insulation class</b>      | II   |
| <b>Protection index</b>      | IP20   |
| <b>Compliance</b>            | CE   |
| <b>Operating temperature</b> | 0° ~ +40 °C  |
| <b>Full load efficiency</b>  | X  |
| <b>Dimmer</b>                | NO, On-Off   |
| <b>Power output</b>          | 220-240 V AC 50/60 Hz  |
| <b>Power supply</b>          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Source info

|                               |   |
|-------------------------------|---|
| <b>Integrated source</b>      | Integrated LED module                     |
| <b>Replaceable source</b>     | Replaceable (by qualified operators only) |
| <b>Power</b>                  | 41 W                                      |
| <b>Emission</b>               | Direct                                    |
| <b>Max consumption</b>        | max 41 W                                  |
| <b>Features LED</b>           | LED SMD                                   |
| <b>CCT LED</b>                | 3000 K                                    |
| <b>Duration LED (t. 25°C)</b> | 20000 h                                   |
| <b>CRI</b>                    | > 80                                      |
| <b>SDCM</b>                   | 3   |
| <b>Light beam</b>             | 115°                                      |
| <b>Light beam flux</b>        | 4350 lm                                   |
| <b>Useful light flux</b>      | 2590 lm                                   |
| <b>Standby power</b>          | < 0.50 W                                  |