



## General info

## Technical - Recessed lights

Indoor ceiling recessed projector with integrated LED sources and direct light emission



<b>Ean</b>	8021696124025
<b>Item</b>	GROOVE FI 30W SQUARE 3000K
<b>Installation</b>	Recessed (Ceiling)
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.96 kg
<b>Volume</b>	0.0036 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.85 kg
<b>Insulation class</b>	II
<b>Protection index</b>	IP20
<b>Compliance</b>	CE
<b>Operating temperature</b>	0° ~ +40 °C
<b>Full load efficiency</b>	X
<b>Dimmer</b>	NO, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	Separate, included Replaceable (by qualified operators only), electronic
<b>Recessed specifications</b>	200 x 200 - h. ≥ 60 , 7-15

## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	Replaceable (by qualified operators only)
<b>Power</b>	30 W
<b>Emission</b>	Direct
<b>Max consumption</b>	max 30 W
<b>Features LED</b>	LED SMD
<b>CCT LED</b>	3000 K
<b>Duration LED (t. 25°C)</b>	30000 h
<b>CRI</b>	> 80
<b>Light beam</b>	110°
<b>Light beam flux</b>	3900 lm
<b>Useful light flux</b>	2250 lm
<b>Photobiological risk</b>	1
<b>Standby power</b>	< 0.50 W