

## General info


### Technical - Systems

Indoor suspended linear fitting with multiple integrated LED sources and direct/indirect light emission

<b>Ean</b>	8021696192710
<b>Item</b>	FLUO BI-EMISSION 1200 3000K BK
<b>Installation</b>	Suspension
<b>Guarantee</b>	5 years
<b>Gross weight</b>	4.88 kg
<b>Volume</b>	0.018311 m <sup>3</sup>

## Technical info

<b>Net weight</b>	2.89 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP20
<b>Compliance</b>	CE
<b>Operating temperature</b>	0° ~ +40 °C
<b>Full load efficiency</b>	X
<b>Dimmer</b>	NO, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	In-built, included Replaceable (by qualified operators only), electronic, tridonic
<b>Accessories not included</b>	Mounting kit (suspension), Dimmable drivers kit, Structure connector



## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	No
<b>Power</b>	27+13 W
<b>Emission</b>	Direct + Indirect
<b>Max consumption</b>	max 40 W
<b>Features LED</b>	LED SMD SAMSUNG
<b>CCT LED</b>	3000 K
<b>Duration LED (t. 25°C)</b>	50000 h
<b>CRI</b>	> 80
<b>SDCM</b>	3
<b>Light beam</b>	105+105°
<b>Light beam flux</b>	5000 lm
<b>Useful light flux</b>	4250 lm
<b>Standby power</b>	< 0.50 W