

Terminal bar

Part no. **KLM**
 275452
EL Number **2456008**
(Norway)

General specifications		
Product name		Eaton xEnergy Basic installation component
Part no.		KLM
EAN		4015082754525
Product Length/Depth		995 millimetre
Product height		10 millimetre
Product width		8 millimetre
Product weight		0.59 kilogram
Compliances		RoHS conform
Product Tradename		xEnergy Basic
Product Type		Accessories
Product Sub Type		Installation component
Delivery program		
Type		Additional equipment
Color		Other
Nominal current		63 A
Number of poles		Single-pole
Technical Data - Mechanical		
Mounting method		Floor standing distribution board Flush mounting Surface mounting Screw
Material		Metal
Number of inputs		2
Number of outputs		140
Connection type		Screwing
Conductor cross section, input - min		1.5 mm ²
Conductor cross section, input - max		16 mm ²
Conductor cross section, input AWG - min		0 mm ²
Conductor cross section, input AWG - max		0 mm ²
Conductor cross section, output - min		1.5 mm ²
Conductor cross section, output - max		16 mm ²
Conductor cross section, output AWG - min		0 mm ²
Conductor cross section, output AWG - max		0 mm ²
Housing material		Brass
Additional information		
Functions		Additional equipment
Suitable for		Fine strand conductors Solid conductors Stranded conductors

Technical data ETIM 8.0

Energy distribution systems (EG000015) / Rail terminal bar (EC000275)		
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Rail terminal bar clamp (ec1@ss10.0.1-27-40-06-03 [AC0369011])		
Number of poles		1
Nominal current	A	63
Connection type		
Mounting method		Screw
Number of inputs		2

Number of outputs			140
Suitable for solid conductors			Yes
Suitable for stranded conductors			Yes
Suitable for fine strand conductors			Yes
Suitable for fine strand conductors without cable end sleeve			No
Suitable for extra fine-strand conductors			No
Suitable for extra fine-strand conductors without cable end sleeve			No
Conductor cross section, input		mm ²	1.5 - 16
Conductor cross section, output		mm ²	1.5 - 16
Conductor cross section, input AWG		mm ²	0 - 0
Conductor cross section, output AWG		mm ²	0 - 0
Contact safe			No
Height		mm	10
Width		mm	8
Depth		mm	995