



<https://www.wago.com/211-502>



Color: бял

Technical data	
Suitable	for wire cross-section 1 ... 2.5 mm ²
Marking method	Thermal transfer
Delivery form	Roll
Delivery form configuration	20 m/roll
Printing device	Smart Printer (thermal transfer printer)

Physical data	
Depth	0,185 mm
Sheathed cable diameter	4,8 mm

Mechanical data	
Mounting type	Sliding on conductor
Shrink rate	2:1
Smear resistance	in conjunction with 258-5005 Ink Ribbon

Material data	
Color	бял
Material	Polyolefin
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	without adhesive
Halogen-free	Yes
Weight	217.1 g
Fire load	0 MJ



Environmental requirements	
Ambient temperature (storage)	+10 ... +25 °C
Ambient temperature (operation)	-55 ... +125 °C
Relative humidity	45 ... 55 %

Commercial data	
eCl@ss 10.0	27-40-04-01
eCl@ss 9.0	27-40-04-01
ETIM 8.0	EC001530
ETIM 7.0	EC001530
PU (SPU)	1 6p.
Packaging type	Box
Country of origin	DK
GTIN	4055143370240
Customs tariff number	39173200910

Downloads	
Documentation	
Operating Instructions	
211-502 Information on printing material	128.08.2020pdf1059.74 KB

1 Compatible Products
1.1 Optional Accessories
1.1.1 Marking
1.1.1.1 Marking devices



Item No.: 258-5000
Термотрансферен принтер; Smart Printer; за пълна маркировка на контролното табло; 300 dpi; с маркировка