



Eikon Next: 16 A IoT connected actuator Next

20593.N

Eikon Next / Devices / Radiofrequency

16 A IoT connected actuator Next

View Wireless connected electronic control device with NO 16 A 100-240 V~ 50/60 Hz relay output, local control with push button or remote control, double technology with Bluetooth® wireless technology 5.0 standard for the realization of View Wireless mesh system and Zigbee 3.0 standard, function for measuring the instant power and load cut-off threshold, RGB LED visible in darkness with brightness control, 100-240 V 50/60 Hz power supply, Next

- Configuration from View Wireless App for Bluetooth technology system and Amazon App for Zigbee technology
- Compatible with Alexa, Google Home and IFTTT, using the dedicated gateway or Zigbee hub



Product Status

3 - Active

Minimum order quantity

1 NR


You may also be interested in



[20597.N - IoT connected gateway 2M Next](#)



[20203.N - 2P+E 16A P17/11 outlet Next](#)



[03925 - Bluetooth Low Energy RF device](#)




Sheets, Manuals, Documentation

- [Foglio istruzioni \(608 kb\)](#)
- [\(666 kb\)](#)
- [Notices techniques \(605 kb\)](#)
- [Hoja de instrucciones \(603 kb\)](#)
- [Instructions sheet \(602 kb\)](#)
- [Φύλλο οδηγιών \(762 kb\)](#)
- [Anwendungshinweise \(606 kb\)](#)
- [Manuale app View Wireless \(12385 kb\)](#)
- [Manuel appli View Wireless \(18781 kb\)](#)
- [Manual app View Wireless \(18410 kb\)](#)
- [Manual View Wireless app \(18450 kb\)](#)
- [Εγχειρίδιο τεχνικού εγκατάστασης \(18614 kb\)](#)
- [Installationsanleitung View Wireless \(18391 kb\)](#)



Video

- [Creating-the-system](#)
- [Customisations](#)
- [Operation-in-Zigbee-mode](#)
- [Bluetooth-wifi-gateway](#)


Drawings



Space view



Backside view



3D View



Technical data

- **Class group:** Installation bus systems
- **Class:** Switch actuator for bus system
- **Bus system KNX:** No
- **Bus system KNX radio:** No
- **Bus system radio frequent:** Yes
- **Bus system LON:** No
- **Bus system Powernet:** No
- **Other bus systems:** None
- **Radio frequent bidirectional:** Yes
- **Mounting method:** Flush mounted (plaster)
- **Width in number of modular spacings:** 1
- **Local operation/hand operation:** Yes
- **With LED indication:** Yes
- **Suitable for C-load:** Yes
- **Max. number of switching contacts:** 1
- **Rated current:** 16 A
- **Rated operating voltage:** 100,00 - 240,00 v
- **Different phases connectable:** No
- **With bus connection:** Yes
- **Modular expandability:** No
- **Degree of protection (IP):** IP40

Certifications

- 00. CE Marking - EU ([download](#))
- 01. IMQ - Italy ([download](#))
- 10. EAC Eurasian Customs Union
- 19. NOM - Mexico
- 29. QCERT - Colombia ([download](#))
- 37. Marking - Morocco
- 40. Bluetooth technology
- 42. Zigbee certified
- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



8 007352 628526
Code 8007352628526
Quantity 1 NR
Dim. 6x5.4x5.2 [cm]
Weight 59 [g]



8 007352 628533
Code 8007352628533
Quantity 60 NR
Dim. 37.5x30x13.5 [cm]
Weight 3,900 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).