



Fuse switch-disconnector, 50A, 1p, 22x51 size

Part no. **VLCE14-3P+N**  
 Catalog No. **192379**

### Delivery program

			For cylindrical fuses
			Up to 50 A Without flashing function
Size			14 x 51
Number of poles			3 + N

### Technical data

#### Electrical

Number of poles			3P+N
Rated operating voltage	$U_e$	V AC	690
Rated operational current	$I_e$	A	50
Rated conditional short-circuit current	$I_e$		100
Rated frequency	f	Hz	50
Utilization category			AC 22 B
Rated impulse withstand voltage	$U_{imp}$	kV	8
Fuse		W	gG: 5, aM: 3

#### Mechanical

Standard front dimension		mm	45
Enclosure height		mm	94
Mounting width		mm	27/per pole
Weight		g	1P 100 1P+N 222 2P 201 3P 308 3P+N 437
Mounting			Quick attachment for top-hat rail IEC/EN 60715
Degree of protection			
Integrated			IP20
Terminals			Lift terminals
Terminal capacities		mm <sup>2</sup>	
Solid		mm <sup>2</sup>	1.5 - 10
Temperature range		°C	-25 ... +60
Specified tightening torque for terminal screws			
Tightening torque		Nm	max. 2
Overvoltage category/pollution degree			-/1
Track resistance			CTI 400

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55

### Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Fuse switch disconnector (EC001040)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnector (ec1@ss10.0.1-27-37-14-01 [AKF058013])			
Version as main switch			No
Version as safety switch			Yes
Max. rated operation voltage $U_e$ AC		V	690

Rated permanent current I <sub>u</sub>	A	50
Rated operation power at AC-23, 400 V	kW	0
Conditioned rated short-circuit current I <sub>q</sub>	kA	100
Rated short-time withstand current I <sub>cw</sub>	kA	0.6
Suitable for fuses		14x51 mm
Number of poles		4
With error protection		No
Type of electrical connection of main circuit		Screw connection
Cable entry		Other
Equipped with connectors		No
Suitable for ground mounting		Yes
Suitable for front mounting 4-hole		No
Suitable for busbar mounting		No
Type of control element		Rocker lever
Position control element		Front side
Motor drive optional		No
Motor drive integrated		No
Version as emergency stop installation		No
Degree of protection (IP), front side		IP20

## Dimensions

