



Fuse-link, low voltage, 6 A, AC 690 V, 80 kA, 14 x 51 mm, gL/gG, IEC



**Part no.** CYLINDRICAL FUSE 14 x 51 6A GG 690V AC  
**Catalog No.** C14G6

**EL-Nummer (Norway)** 1600273

**Delivery program**

|                              |   |    |  |
|------------------------------|---|----|--|
| Product range                |   |    | Fuse   |
| Basic function               |   |    | Fuse-link  |
| Field of application         |   |    | low voltage  |
| Rated current                | I | A  | 6  |
| Rated voltage                |   |    | AC 690 V   |
| Size                         |   |    | 14 x 51 mm   |
| Utilization category         |   |    | gL/gG  |
| Breaking Capacity            |   | kA | 80   |
| usable for size/applications |   |    | for industrial applications<br>for general purpose use |
| Standard/Approval            |   |    | IEC  |
| Shape                        |   |    | cylindrical  |
| Standards/Regulations        |   |    | IEC 60269-2  |

**Technical data ETIM 7.0**

|   |  |    |   |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)   |  |    |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013]) |  |    |   |
| Size  |  |    | 14x51 mm                                      |
| Rated voltage   |  | V  | 690 - 690                                     |
| Rated voltage   |  |    | Other   |
| Voltage type  |  |    | AC  |
| Utilization category  |  |    | gL/gG (cable protection/equipment protection) |
| Rated operating frequency   |  | Hz | 45 - 62                                       |
| Nominal current   |  | A  | 6   |
| With striker  |  |    | No  |
| Release characteristic  |  |    | Other   |
| Breaking capacity   |  | kA | 80  |