




**Undervoltage release, 230 V, non-delayed, 1HP**

**Part no.** Z-USA/230  
**Catalog No.** 248289  
**Alternate Catalog No.** Z-USA/230  
**EL-Nummer (Norway)** 0001609472

**Delivery program**

Basic function		Accessories for miniature circuit-breaker
Basic function accessories		Undervoltage release
Application		Switchgear for industrial and advanced commercial applications
Tripping	s...	non-delayed
Product range		Accessory
Side mounting		for fitting on left to: FAZ
Contact sequence		

**Design verification as per IEC/EN 61439**

Technical data for design verification		
Operating ambient temperature min.	°C	-5
Operating ambient temperature max.	°C	40

**Technical data ETIM 7.0**

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecI@ss10.0.1-27-14-35-02 [AKE327013])		
Device fitting		Universal
Additional equipment		Under voltage coil
Attached at delivery		No
Assembly width (TE)		1
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	A	0
Rated voltage	V	230
Voltage type for actuating		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		1
Suitable for max. current main contact unit	A	0

## Dimensions

