



With the PFC200 Controller as its central component, the Linux® Starter Kit provides an entry to the world of open programming. In addition to its scalability through the open-source community, the primary advantage of having a controller with an open-source operating system is its continual development and maintenance.

Besides the PFC200, other components of the starter kit include input and output modules, a power supply, a switching module and the accessories needed to start programming immediately with Linux®.

Additional information on Linux® is available at: <https://www.wago.com/linux>.

The Linux® advanced Starter Kit includes:

- Controller PFC200; 2nd Generation; 2 x ETHERNET, RS-232/-485: 750-8212
- 2-Channel Digital Input; 24 VDC; 3 ms: 750-400
- 2-Channel Digital Output; 24 VDC; 0.5 A: 750-501
- End Module: 750-600
- Classic Power Supply; 24 VDC output voltage; 1 A: 787-1602
- Switching Module; 2-way DI simulator: 288-863
- Operating Tool; Type 2; (3.5 x 0.5) mm blade: 210-720
- Operating Tool; Type 1; (2.5 x 0.4) mm blade: 210-719
- Patch Cable; 1.0 m

Technical data

Communication

Modbus (TCP, UDP)
 ETHERNET
 Modbus® RTU
 RS-232 serial interface
 RS-485 interface
 EtherNet/IP™ Adapter (slave), library for **e!RUNTIME**
 EtherCAT® master (**requires an additional license**)
 MQTT

ETHERNET protocols

DHCP
 DNS
 NTP
 FTP
 FTPS
 SNMP
 HTTP
 HTTPS
 SSH

Programming environment

e!COCKPIT (based on CODESYS V3)
 WAGO-I/O-PRO V2.3 (based on CODESYS V2.3)

Mechanical Data

Weight	892.6 g
--------	---------

Environmental requirements

Fire load	44.371 MJ
-----------	-----------

Commercial data

ETIM 8.0	EC002581
ETIM 7.0	EC002581
PU (SPU)	1 бр.
Packaging type	Box
Country of origin	DE
GTIN	4055144060966
Customs tariff number	85371091990