

CAT. N° 4 192 25


**MCB RX<sup>3</sup> 6000 - 2P - 230/400 V~ - 20 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS**


Pack (number of units)	6
Volume (dm <sup>3</sup> )	1,864
Weight (g)	1 557,00

**Product characteristics**
**2-pole 230/400 V~**

- C curve
- Nominal rating In : 20 A
- Number of modules : 2

**General characteristics**
**MCBs RX<sup>3</sup> 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve**

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
  - 6000 - IEC 60898-1 - 230/400 V~
  - 6 kA - IEC 60947-2 - 230/400 V~
  - 10000 - IEC 60898-1 - 127/220 V~
  - 10 kA - IEC 60947-2 - 127/220 V~

**Documentation**
 **Catalogue pages & additional information**

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB-IT-14270](#)
- [VDE-40041249](#)

 **Installation & technical data**

- [F01909EN-02](#)

 **Environmental product profile**

- [LGRP-00683-V01](#)