



Filament

- Classic light bulb shape ensures an easy replacement
- Instant 100% light when switched on and no startup time
- No UV / IR radiance so there is less risk of damage



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Weight (kg/pc)
500010000600	Mini Globe (P, G45), On-Off LED-E-P45-FILA-E14-2.8W-2700K-CL	GLS 25W	2.8	250	89	2700	0.01

Packaging Information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
500010000600	LED-E-P45-FILA-E14-2.8W-2700K-CL	85395200	45x45x91	0.04	6945730405234	1

Technical Specifications


Lifetime (L70)	15,000 h
On-/Off-cycles	100,000
Dimmability	On-Off
Beam angle	360°
Finishing	Clear
Colour rendering index (CRI)	≥ 80

Electrical Supply


Frequency	50/60 Hz
Nominal voltage	220-240 V
DC input voltage	No

Ambient Conditions

Operating temperature	-20-+40°C
Application temperature	+25°C
Storage environment	-25-+50°C



Dimensional Drawing (mm)



Photometric Data

