



Downlight Compact

- Stylish and compact LED downlight
- Sturdy full metal housing
- Integrated driver for easier installation
- Low height of only 35mm
- IP44 on light emitting side



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Weight (kg/pc)
On-Off							
540001291100	LEDDownlightCo-E Rd125-14W-830	CFL 1x26W	14	1190	85	3000	0.14

Accessories



140060650
LEDDownlightRc-HZdim-Adapter-125-150



542098030700
Junction-Box-WH

Packaging Information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
540001291100	LEDDownlightCo-E Rd125-14W-830	94051190	145x50x148	0.18	6941408895680	1
140060650	LEDDownlightRc-HZdim-Adapter-125-150	94059900	175x175x0.8	0.15	6956321894160	1
542098030700	Junction-Box-WH	85369010	43x103.4x26	0.06	6941408868684	1



Technical Specifications	
Lifetime (L70)	50,000 h
Lifetime (L80)	30,000 h
On-/Off-cycles	100,000
Colour consistency (SDCM)	3
Dimmability	On-Off
Beam angle	100°
Finishing	White RAL9003
Colour rendering index (CRI)	≥ 80
IP front side	IP44
IP recessed part	IP20
Impact strength	IK02
Protection class	II
Risk group (EN 62471)	RG0
With control gear	Yes
Glow wire test	650°C
Displacement factor (DF)	≥ 0.9


Electrical Supply	
Frequency	50/60 Hz
Nominal voltage	220-240 V
DC input voltage	No
230V Cable length	0.3 m

Mechanical Properties	
Housing material	Aluminium
Optical material	Polycarbonate


Ambient Conditions	
Operating temperature	-10~+45°C
Application temperature	+25°C
Storage environment	-25~+45°C

Dimensional Drawing (mm)

LEDDownlightCo-E Rd125



Photometric Data



Installation Opening Drawing (mm)

