

CAT. N° 4 191 59



## MCB RX<sup>3</sup> 6000 - 2P - 230/400 V~ - 20 A - B CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

|                           |          |
|---------------------------|----------|
| Pack (number of units)    | 6        |
| Volume (dm <sup>3</sup> ) | 1,864    |
| Weight (g)                | 1 559,00 |

### Product characteristics

#### 2-pole 230/400 V~

- B curve
- Nominal rating I<sub>n</sub> : 20 A
- Number of modules : 2

### General characteristics

#### MCBs RX<sup>3</sup> 6000 - thermal magnetic MCBs from 6 A to 63 A - B curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type and fork type supply busbars
- Breaking capacity:
  - 6000 - IEC 60898-1 - 230/400 V~
  - 6 kA - IEC 60947-2 - 230/400 V~
  - 10000 - IEC 60898-1 - 127/220 V~
  - 10 kA - IEC 60947-2 - 127/220 V~

### Documentation

#### Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

#### Agreements & certificates of conformity

- [OC / CB-IT-14270](#)
- [VDE-40041249](#)

#### Installation & technical data

- [F01909EN-02](#)

#### Environmental product profile

- [LGRP-00683-V01](#)