

**ECTG1216**



**RIGID CONDUIT 22211 Ø16 mm - 3 m**

Conduits and fittings > Conduits > Rigid conduits > Series tg12  
- pvc - class 22211 - 320 n > plastic conduits > 3 meters -  
length



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**

|            |             |    |         |                     |
|------------|-------------|----|---------|---------------------|
| UL94<br>V0 | GWT<br>960° | CE | RoHS II | MADE<br>IN<br>ITALY |
|------------|-------------|----|---------|---------------------|

**Norms**

EN 61386-1 EN 61386-21

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC001174 - Plastic installation tube**

|   |                           |  |                           |  |       |
|---|---------------------------|--|---------------------------|--|-------|
| <b>Flush-mounted installation</b>                         | Yes                       | <b>Material</b>                                      | Polyvinyl chloride (PVC)  | <b>Halogen free</b>                      | No    |
| <b>Colour</b>   | Grey                      | <b>RAL-number</b>                                    | 7035                      | <b>UV resistant</b>                      | Yes   |
| <b>Suitable for underground installation</b>              | No                        | <b>Operating temperature</b>                         | -5-60 °C                  | <b>Bending strength</b>                  | Rigid |
| <b>Compressive strength class according to EN 61386-1</b> | Light (class 2 / 1 Joule) | <b>Impact strength class according to EN 61386-1</b> | Light (class 2 / 1 Joule) | <b>With sleeve</b>                       | No    |
| <b>Fire retardant version</b>                             | Yes                       | <b>Surface mounting</b>                              | Yes                       | <b>Suitable for installation on wood</b> | Yes   |
| <b>Suitable for hollow wall installation</b>              | Yes                       | <b>Suitable for concrete installation</b>            | No                        | <b>Machine and systems installation</b>  | No    |
| <b>Suitable for underfloor installation (screed)</b>      | No                        | <b>Suitable for outdoor installation</b>             | No                        | <b>Inner diameter</b>                    | 14 mm |
| <b>Outer diameter</b>                                     | 16 mm                     | <b>High conducting inner coating</b>                 | No                        | <b>With metre indication</b>             | No    |

## Barcode



8054320285120

### Cardboard

102 MT

6.5994 [kg]



8057711598496

### Pallet

3162 MT

3x0.62x0.58 [m]

204.5814 [kg]