

# Specifications

## Eaton 211809

Eaton Moeller series xEffect - AZ MCB.  
Miniature circuit breaker (MCB) AZ, 1 pole,  
Tripping characteristic: C, Rated current In:  
125 A

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series xEffect - AZ MCB
<b>CATALOG NUMBER</b>	211809
<b>EAN</b>	4015082118099
<b>PRODUCT LENGTH/DEPTH</b>	90 mm
<b>PRODUCT HEIGHT</b>	75 mm
<b>PRODUCT WIDTH</b>	27 mm
<b>PRODUCT WEIGHT</b>	0.218 kg
<b>COMPLIANCES</b>	CE Marked RoHS conform
<b>CERTIFICATIONS</b>	IEC/EN 60947-2 EN45545-2 IEC 61373
<b>MODEL CODE</b>	AZ-C125



Powering Business Worldwide

## Product specifications

<b>USED WITH</b>	AZ Miniature circuit breaker
<b>AMPERAGE RATING</b>	125 A
<b>VOLTAGE RATING</b>	230 V AC / 400 V AC
<b>FEATURES</b>	Additional equipment possible
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to

## Resources

<b>APPLICATION NOTES</b>	<a href="#">eaton-quality-standards-for-railway-applications-application-paper-ap003005en-en-us.pdf</a> <a href="#">eaton-maximum-cable-lengths-for-eatons-protective-devices-brochure-br034006en-en-us.pdf</a>
<b>BROCHURES</b>	<a href="#">eaton-pdd-railrolling-stock-brochure-br011002en-en-us.pdf</a> <a href="#">eaton-xeffect-az-mcb-characteristic-curve-002.jpg</a> <a href="#">eaton-mcb-xeffect-az-characteristic-curve-002.eps</a> <a href="#">eaton-mcb-tripping-characteristic-xeffect-az-characteristic-curve.eps</a>
<b>CHARACTERISTIC CURVE</b>	<a href="#">eaton-xeffect-az-mcb-characteristic-curve-004.jpg</a> <a href="#">eaton-mcb-xeffect-az-characteristic-curve.eps</a> <a href="#">eaton-mcb-current-xeffect-az-characteristic-curve-002.eps</a> <a href="#">eaton-mcb-current-xeffect-az-characteristic-curve.eps</a>
<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">DA-DC-03_AZ</a> <a href="#">eaton-mcb-xeffect-az-dimensions.eps</a> <a href="#">eaton-xpole-mmct-mcb-dimensions.jpg</a>
<b>DRAWINGS</b>	<a href="#">eaton-mcb-faz-xeffect-faz-3d-drawing.eps</a> <a href="#">eaton-xeffect-az-mcb-3d-drawing-002.jpg</a> <a href="#">eaton-xeffect-az-mcb-3d-drawing.jpg</a>
<b>ECAD MODEL</b>	<a href="#">DA-CE-ETN.AZ-C125</a>

	be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>FRAME</b>	45 mm
<b>POLLUTION DEGREE</b>	2
<b>MOUNTING METHOD</b>	Top-hat rail IEC/EN 60715
<b>DEGREE OF PROTECTION</b>	IP20 IP40 (when fitted)
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>	11.89 W 11.9 W
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	4 kV
<b>ADMISSIBLE BACK-UP FUSE - MAX</b>	200 A gL/gG
<b>TERMINAL PROTECTION</b>	Finger and hand touch safe, DGUV VS3, EN 50274
<b>TERMINALS (TOP AND BOTTOM)</b>	Lift terminals
<b>TRIPPING CHARACTERISTIC</b>	C
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	55 °C

<b>INSTALLATION INSTRUCTIONS</b>	<a href="#">IL019148ZU</a>
<b>MCAD MODEL</b>	<a href="#">DA-CD-az_1p</a> <a href="#">DA-CS-az_1p</a>
<b>WIRING DIAGRAMS</b>	<a href="#">eaton-xpole-mm4-6-m-mcb-wiring-diagram-002.jpg</a> <a href="#">eaton-mcb-xeffect-faz-wiring-diagram.eps</a>

<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>BUILT-IN DEPTH</b>	75 mm
<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX</b>	50 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN</b>	2.5 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX</b>	50 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN</b>	2.5 mm <sup>2</sup>
<b>CURRENT LIMITING CLASS</b>	3
<b>ENCLOSURE WIDTH</b>	90 mm
<b>FREQUENCY RATING - MAX</b>	60 Hz
<b>FREQUENCY RATING - MIN</b>	50 Hz
<b>HEAT DISSIPATION CAPACITY</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT</b>	11.9 W
<b>DIRECTION OF INCOMING SUPPLY</b>	As required
<b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>	1.5
<b>VOLTAGE RATING AT DC</b>	60 V DC (per pole)
<b>VOLTAGE TYPE</b>	AC
<b>OVERVOLTAGE CATEGORY</b>	III
<b>NUMBER OF POLES</b>	Single-pole
<b>LIFESPAN, ELECTRICAL</b>	10000 operations
<b>RELEASE CHARACTERISTIC</b>	C
<b>TYPE</b>	<ul style="list-style-type: none"> <li>• AZ</li> <li>• Miniature circuit breaker</li> </ul>
<b>SPECIAL FEATURES</b>	Ambient temperature hint:

a 1 °C increase results in a 0.5% linear reduction of current carrying capacity

**APPLICATION**

- Switchgear for industrial and advanced commercial applications
- xEffect - Switchgear for industrial and advanced commercial applications

**MOUNTING WIDTH** 27 mm

**SELECTIVITY CLASS** 3

**MOUNTING WIDTH PER POLE** 27 mm

**NUMBER OF POLES (PROTECTED)** 1

**NUMBER OF POLES (TOTAL)** 1

**OPERATIONAL SWITCHING CAPACITY** 20 kA

**RATED INSULATION VOLTAGE (UI)** 440 V

**RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)** 125 A

**RATED OPERATIONAL VOLTAGE (UE) - MAX** 230 V

**RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 230 V** 0 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 400 V** 0 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 230 V** 15 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 400 V** 15 kA

**RATED SWITCHING CAPACITY (IEC/EN 60947-2)** 15 kA

**STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT** 0 W

---

**TERMINAL CAPACITY  
(CONTROL CABLE)**

---

2.5 mm<sup>2</sup> - 50 mm<sup>2</sup>

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.