

**Technical data**

Main product function	"Alu-Plus" contact paste
-----------------------	--------------------------

Material data

Fire load	0 MJ
Weight	35.3 g

Commercial data

Product Group	2 (Terminal Block Accessories)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 7.0	EC002848
ETIM 6.0	EC002848
PU (SPU)	20 (5) Stück
Packaging type	Box
Country of origin VKOrg Germany	DE
GTIN	4017332133890
Customs tariff number VKOrg Germany	34039900900

Изтегляния**Documentation**

Bid Text			
249-130	17.05.2017	doc 23.50 KB	
249-130	19.02.2019	xml 2.49 KB	

CAD/CAE-Data


CAE data

EPLAN Data Portal
249-130



Бележки за инсталиране



Application



WAGO Rail-Mount Terminal Blocks (up to 4 mm²/12 AWG)
For each conductor entry: Insert nozzle of the "Alu-Plus" syringe in every open conductor entry hole (one after the other).

Press plunger down until "Alu-Plus" has filled all conductor entry holes.

Application





WAGO Lighting Connectors
Push nozzle of the "Alu-Plus" syringe first into the circular entry and then into the square conductor entry hole of the WAGO Lighting Connector.

Press the plunger down until "Alu-Plus" has filled both entry holes.

Note: Not suitable for higher temperature applications!

Application



1. Push nozzle of the "Alu-Plus" syringe into every open conductor entry hole (one after the other).

2. Press plunger down until "Alu-Plus" has filled all conductor entry holes.