

ECGX32M



**IP65 SPIRAL CONDUIT 32-BOX JOINT-
M THREAD-40 mm - GREY**



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Conduits and fittings > Accessories and fittings > Joints and fittings > Series gx - ip65 fittings for spiral conduits > Coupler spiral conduit - box > Metric pitch - grey

Technical Symbols/Marks/Approvals

| | | | | | | | |
|------|---------|----------|----|---------|-----|----|---------------|
| IP65 | UL94 V2 | GWT 750° | CE | RoHS II | CCC | UL | MADE IN ITALY |
|------|---------|----------|----|---------|-----|----|---------------|

Norms

EN 61386-1 EN 61386-23 UL 1696

Etim

GROUP EG000003 - Protective hose systems
CLASS EC001178 - Screw connection for protective plastic hose

| | | | | | |
|---|--------------------|-----------------------------------|-----------|---|-----------------|
| Degree of protection (IP) | IP65 | Colour | Grey | Model | Straight |
| Working temperature | -25-65 °C | Nominal diameter | 32 mm | Thread length | 40 mm |
| Material sealing | No sealing | Revolving thread | Yes | Construction type | Internal thread |
| Type of connection | Thread | Thread connection size | M40 x 1.5 | One-piece | Yes |
| Material screw gland | Polypropylene (PP) | Lowest inner diameter hose | 32 mm | Approved in combination with protective conduit according to DIN EN 61386-23 | Yes |
| Approved in combination with protective conduit UR | Yes | | | | |

Documentation available for download

Certification

Certificato UL
GUAINA E173313-
2021.pdf

Certification

Serie Guaine e
raccordi
IMQ_CA02.06109_
2023.pdf

Barcode



8050880889716

Pack

10 NR

0.444 [kg]



8057711594856

Cardboard

90 NR

3.996 [kg]