

XTINY RECESSED|SURFACE

ARELUX S.R.L.
Alexei Tolstoy street, nr. 12, Bacău - 600093, ROMÂNIA.
Tel: +40 0234 514 492 / 546 620. Fax: +40 0234 546 677.

XT01RLC SBK

www.arelux.ro

10/2023

GENERAL INFORMATION / INFORMAȚII GENERALE / INFORMAZIONI GENERALI

Code	Finishing	Input voltage	Operating temp.	Weight
XT01RLC SBK	Sand black	48V DC	-30 ÷ +45 °C	0,04 kg

Description / Descriere / Descrizione

EN - Linear connector, mechanical and electrical, for two recessed XTINY profiles.

RO - Conector liniar, mecanic și electric, pentru două profile încastrate XTINY.

IT - Connettore lineare, meccanico ed elettrico, per due profili XTINY da incasso.

Housing / Corp / Corpo

EN - Housing of Sand black aluminum and polycarbonate.

RO - Carcasa din policarbonat și aluminiu de culoare neagră, finisaj sablat.

IT - Carcassa in policarbonato e alluminio bianco sabbiato.

Electric gear / Aparataj de alimentare / Alimentazione

EN - Electrical circuit for 48V DC with two electrical contacts at each end.

RO - Circuit electric de 48V DC cu cate două contacte electrice la fiecare capăt.

IT - Circuito elettrico per 48V DC con due contatti elettrici a ciascuna estremità.

