



## T8 Tube Performer G2

- Single-ended full IEC compliant LED Tube with patented driver
- Improved efficacy of 170 lm/W
- Retrofit existing T8 lamps with EM ballast installations ONLY!
- No warm-up time, 100% light instantly when switched on
- Full glass body



SAFE AND EASY INSTALLATION: ONLY USE WITH LED DUMMY STARTER.  
Tubes are NOT suitable for serial installation.

## Specifications

| Item Code    | Item Description               | Equivalent to (W) | Power (W) | Lumen (lm) | Efficacy (lm/W) | CCT (K) | Net Weight (kg/pc) |
|--------------|--------------------------------|-------------------|-----------|------------|-----------------|---------|--------------------|
| 802003034600 | LEDTubeT8-EMB-P2 L1200 16W-865 | TL 1x58W          | 16        | 2720       | 170             | 6500    | 0.21               |

## Packaging information

| Item         |                                |            | Box                     |                      |               |        |
|--------------|--------------------------------|------------|-------------------------|----------------------|---------------|--------|
| Item Code    | Item Description               | EU HS Code | Dimensions (mm) (LxWxH) | Gross Weight (kg/pc) | EAN           | pc/box |
| 802003034600 | LEDTubeT8-EMB-P2 L1200 16W-865 | 85395200   | 1200x28x28              | 0.35                 | 6937209622495 | 1      |

### Technical Specifications

|                              |          |
|------------------------------|----------|
| Lifetime (L70)               | 50,000 h |
| On-/Off-cycles               | 100,000  |
| Dimmability                  | On-Off   |
| Beam angle                   | 220 °    |
| Colour rendering index (CRI) | > 80     |
| Fitting                      | G13      |

### Electrical Supply


|                  |             |
|------------------|-------------|
| Frequency        | 50 - 60 Hz  |
| Nominal voltage  | 220 - 240 V |
| DC input voltage | No          |

### Mechanical Properties

### Ambient Conditions

|                         |             |
|-------------------------|-------------|
| Operating temperature   | -20 - 45 °C |
| Application temperature | 25 °C       |
| Storage environment     | -25 - 50 °C |

# Installation Possibilities



Single-ended connection

# Photometric Data

