



T8 Tube Performer G2

- Single-ended full IEC compliant LED Tube with patented driver
- Improved efficacy of 170 lm/W
- Retrofit existing T8 lamps with EM ballast installations ONLY!
- No warm-up time, 100% light instantly when switched on
- Full glass body



SAFE AND EASY INSTALLATION: ONLY USE WITH LED DUMMY STARTER.
Tubes are NOT suitable for serial installation.

Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen (lm)	Efficacy (lm/W)	CCT (K)	Net Weight (kg/pc)
802003034700	LEDTubeT8-EMB-P2 L1200 16W-830	TL 1x58W	16	2560	160	3000	0.21

Packaging information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg/pc)	EAN	pc/box
802003034700	LEDTubeT8-EMB-P2 L1200 16W-830	85395200	1200x28x28	0.35	6937209622471	1

Technical Specifications

Lifetime (L70)	50,000 h
On-/Off-cycles	100,000
Dimmability	On-Off
Beam angle	220 °
Colour rendering index (CRI)	> 80
Fitting	G13

Electrical Supply

Frequency	50 - 60 Hz
Nominal voltage	220 - 240 V
DC input voltage	No

Mechanical Properties

Ambient Conditions

Operating temperature	-20 - 45 °C
Application temperature	25 °C
Storage environment	-25 - 50 °C

Installation Possibilities



Single-ended connection

Photometric Data

