

XFIVE RECESSED|SURFACE**FVRS01LC MBK**

Application field / Finishing	Indoor / Black
Protection class	Classe III
IP / IK rating	IP40
Input voltage	48V DC
Ambient temperature	-20 ÷ +45 °C
Warranty	5 years
Weight	0,03 kg

Description / Descriere / Descrizione

EN - Electrical, linear connector of black polycarbonate, for two recessed or surface XFIVE profiles.

RO - Element de conexiune electrică, liniară, din policarbonat negru, pentru două profile încastrate sau aparente XFIVE.

IT - Connettore elettrico lineare, in policarbonato nero, per due profili XFIVE da incasso o da superficie XFIVE.

Electric gear / Aparataj de alimentare / Alimentazione

EN - Electrical circuit for 48V DC with two electrical contacts for the track.

RO - Circuit electric de 48V DC cu două contacte electrice pentru profil.

IT - Circuito elettrico per 48V DC con due contatti elettrici per profilo.

Standards

EN 60598-1:2021, EN 60598-2-1:2021, EN 60529:1992 + A2:2013, EN 55015:2019 + A11:2020, EN 61000-3-2:2019, EN 61000-3-3:2013 + A1:2019, EN 61547:2023, EN 62717:2017+A2:2019, EN 62722-2-1:2023.

