

XFIVE RECESSED|SURFACE**FVRS01PC MBK**

Application field / Finishing	Indoor / Black
Protection class	Classe III
IP / IK rating	IP40
Input voltage	48V DC
Ambient temperature	-20 ÷ +45 °C
Warranty	5 years
Weight	0,01 kg

Description / Descriere / Descrizione

EN - Power supply element of black polycarbonate, for the recessed or surface profiles XFIVE, with power supply cable, for connection to the 48V DC driver.

RO - Element de alimentare din polycarbonat negru, pentru profilele încastrate sau aparente XFIVE, cu cablu de alimentare, care asigură legătura cu alimentatorul de 48V DC.

IT - Elemento di alimentazione in polycarbonato nero, per profili da incasso o da parete/soffitto XFIVE, con cavo di alimentazione, per il collegamento all'alimentatore da 48V DC.

Electric gear / Aparataj de alimentare / Alimentazione

EN - Electrical circuit for 48V DC with two electrical contacts for the track.

RO - Circuit electric de 48V DC cu două contacte electrice pentru profil.

IT - Circuito elettrico per 48V DC con due contatti elettrici per profilo.

Standards

EN 60598-1:2021, EN 60598-2-1:2021, EN 60529:1992 + A2:2013, EN 55015:2019 + A11:2020, EN 61000-3-2:2019, EN 61000-3-3:2013 + A1:2019, EN 61547:2023, EN 62717:2017+A2:2019, EN 62722-2-1:2023.

