


















**Data Sheet | Item Number: 887-932**  
**Splicing Connector Set; L-BOXX® 102; 221, 2273, 207 Series**

<https://www.wago.com/887-932>



**This item includes:**

 <b>Item No.: 221-412</b> Splicing connector with levers; for all conductor types; max. 4 mm <sup>2</sup> ; 2-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm <sup>2</sup> ; transparent	 <b>Item No.: 221-413</b> Splicing connector with levers; for all conductor types; max. 4 mm <sup>2</sup> ; 3-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm <sup>2</sup> ; transparent	 <b>Item No.: 221-415</b> Splicing connector with levers; for all conductor types; max. 4 mm <sup>2</sup> ; 5-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm <sup>2</sup> ; transparent	 <b>Item No.: 2273-202</b> PUSH WIRE® splicing connector; for solid conductors; max. 2.5 mm <sup>2</sup> ; 2-conductor; transparent housing; white cover; Surrounding air temperature: max 60°C (T60); 2,50 mm <sup>2</sup> ; transparent
 <b>Item No.: 2273-203</b> PUSH WIRE® splicing connector; for solid conductors; max. 2.5 mm <sup>2</sup> ; 3-conductor; transparent housing; orange cover; Surrounding air temperature: max 60°C (T60); 2,50 mm <sup>2</sup> ; transparent	 <b>Item No.: 2273-205</b> PUSH WIRE® splicing connector; for solid conductors; max. 2.5 mm <sup>2</sup> ; 5-conductor; transparent housing; yellow cover; Surrounding air temperature: max 60°C (T60); 2,50 mm <sup>2</sup> ; transparent	 <b>Item No.: 2273-500</b> 2 Mounting carrier; for single- and double-row con.; 2273 Series; for DIN-35 rail mounting/screw mounting; orange	 <b>Item No.: 221-500</b> 2 Mounting carrier; 221 Series - 4 mm <sup>2</sup> ; for DIN-35 rail mounting/screw mounting; orange
 <b>Item No.: 221-500/000-006</b> 1 Mounting carrier; 221 Series - 4 mm <sup>2</sup> ; for DIN-35 rail mounting/screw mounting; blue	 <b>Item No.: 221-500/000-053</b> 1 Mounting carrier; 221 Series - 4 mm <sup>2</sup> ; for DIN-35 rail mounting/screw mounting; dark gray-yellow	 <b>Item No.: 221-942/000-006</b> 5 Jumper; for conductor entry; 2-way; insulated; blue	 <b>Item No.: 221-941</b> 5 Jumper; for conductor entry; 2-way; insulated; dark gray
 <b>Item No.: 207-1333</b> 1 Gelbox; Branch; for cables; with gel; 221, 2x73 Series; max. 4 mm <sup>2</sup> connectors; without splicing connectors; Size 3; gray	 <b>Item No.: 207-1332</b> 1 Gelbox; Branch; for cables; with gel; 221, 2x73 Series; max. 4 mm <sup>2</sup> connectors; without splicing connectors; Size 2; gray	 <b>Item No.: 207-1331</b> 1 Gelbox; Branch; for cables; with gel; 221, 2x73 Series; max. 4 mm <sup>2</sup> connectors; without splicing connectors; Size 1; gray	 <b>Item No.: 221-2411</b> 60 Inline splicing connector with levers; for all conductor types; max. 4 mm <sup>2</sup> ; 2-conductor; transparent housing; Transparent cover; Surrounding air temperature: max 85°C (T85); 4,00 mm <sup>2</sup> ; transparent
 <b>Item No.: 221-2503</b> 1 Mounting carrier with strain relief; 3-way; for inline splicing connector with lever; for screw mounting; gray			

## Notes

General safety information

**NOTICE: Observe installation and safety instructions!**

- **Only to be used by electricians!**
- Do not work under voltage/load!
- Use only for proper use!
- Observe national regulations/standards/guidelines!
- Observe technical specifications for the products!
- Observe the number of permissible potentials!
- Do not use damaged/dirty components!
- Observe conductor types, cross-sections and strip lengths!
- Insert conductor until it hits the product's backstop!
- Use original accessories!

**To be sold only with installation instructions!**

## Physical data

Width	445 mm / 17.519 inches
Height	118 mm / 4.646 inches
Depth	358 mm / 14.094 inches

## Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Fire load	18.665 MJ
Weight	3453.1 g

## Commercial data

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	QU
GTIN	4066966194944
Customs tariff number	80808080888

## Product Classification

UNSPSC	39121409
ETIM 9.0	EC000446
ETIM 10.0	EC000524
ECCN	NO US CLASSIFICATION

## Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product  
Compliance 887-932

