



LinkedGo Smart HVAC thermostat

Specifications

Scope of use:	ST800 series products are two-in-one products for cooling and heating. They are mainly used for indoor temperature control of central air-conditioning fan-coil systems or floor heating systems.
Product model:	ST802-B series
Input voltage:	90–240 V AC 50/60 Hz
Load current:	2 A resistive load, 1 A inductive load
Temperature control range:	5 to 35°C
Working environment:	-10°C to +55°C
Protection level:	IP20
Wi-Fi	
Protocol:	802.11 b/g/n
RF band:	2412 - 2484 MHz
Max. RF power:	< 20 dBm
Range:	Up to 30 m / 100 ft indoors and 50 m / 160 ft outdoors (Depends on local conditions)
Bluetooth	
Protocol:	5
RF band:	2402 - 2480 MHz
Range:	Up to 10 m / 33 ft indoors and 30 m / 100 ft outdoors (Depends on local conditions)
Smart capabilities	
Schedules:	20
Webhooks (URL actions):	20 with 5 URLs per hook
Scripting:	No
MQTT:	Yes
UDP:	Yes
Advanced schedules:	Yes
KVS (Key-Value Store):	Yes

Download user and safety guide

Device compliance

Company

Shelly certified Installers

Find a Shelly official Reseller

Help

Customer Support

Open a support ticket

Learn

Shelly X

Knowledge base

Information

Delivery & Returns

General Terms & Conditons