

## USB charger with 2 type C - 20W

BT-K4192CC | EAN: 8005543819029



Product Line

Living NOW, Bticino

### DESCRIPTION

USB charger with 2 type C ports for charging single electronic devices up to 20W or simultaneous charging of two devices.- 100-240 V 50-60 Hz DIRECT power supply- Output voltage 5V - 1 module

### PRODUCT CHARACTERISTICS

- USB Type A and type C chargers with 5 Vd.c. voltage for fast charging of a device simultaneously, 100-240 v 50-60 Hz, 1 module
- The device must be completed with the specific USB cover
- Screw and plate terminals
- Easy installation and removal of the mechanism on the support frame thanks to the new generation of plastic hooking system

- DIRECT POWER 100-240 V 50-60 Hz - 1 module

## TECHNICAL CHARACTERISTICS

|                                        |                         |                                           |                   |
|----------------------------------------|-------------------------|-------------------------------------------|-------------------|
| Model                                  | Other                   | Number of ports USB-A                     | 0                 |
| Number of ports USB-C                  | 1                       | Operating voltage (Min-Max)               | 100-240 V         |
| Frequency (Min-Max)                    | 50-60 Hz                | Max. output current                       | 3000 mA           |
| Output voltage (Min-Max)               | 5-12 V                  | Power consumption                         | 0.048 W           |
| Connection type                        | Screwed terminal        | Mounting method                           | Flush-mounted     |
| Colour                                 | Black                   | RAL-number                                | 7015              |
| Device width                           | 22 mm                   | Device height                             | 45 mm             |
| Device depth                           | 41 mm                   | Min. depth of built-in installation box   | 40 mm             |
| Suitable for degree of protection (IP) | IP20                    | degree of impact strength (IK)            | IK04              |
| Antimicrobial treatment                | No                      | Wireless                                  | No                |
| Built-in depth                         | 33 mm                   | Operating / setting temperature (Min-Max) | -5-35 °C          |
| Storage temperature (Min-Max)          | -10-70 °C               | Voltage type                              | AC                |
| Power Delivery                         | Yes                     | USB Output Power                          | 20                |
| Supply current (Min-Max)               | 0.5-0.5 A               | Mandatory neutral                         | Yes               |
| Terminal marking indication            | Yes                     | Stress test conformity (1000V)            | No                |
| Halogen free                           | Yes                     | Number of terminals                       | 2                 |
| Terminals capacity (Min-Max)           | 1.5-2.5 mm <sup>2</sup> | Cable nature for connection               | Flexible or rigid |
| Cable section (Min-Max)                | 1.5-2.5 mm <sup>2</sup> | Number of modules (module system)         | 1                 |

## THE PRODUCT'S BENEFITS

---

### Installation

Further improvement of the installation and removal in support thanks to the new generation of plastic hooks.

### Usage

It is the ideal charger for smartphone, tablet or powerbank.

### Advantages

- It is coordinated with the L.NOW aesthetic

## USAGE RECOMMENDATIONS

---

For internal use only. Load limited to 20 W \*\* not suitable for loading a laptop

## DOCUMENTATION

---

### CAD & design SPECS / BIM

---

**BIM Data**   **BIM-BTICINO-LIVING-NOW-2026-ENGLISH** | RVT (163.3 MB)