

# Specifications



## Eaton 286573

Eaton Moeller series xPole - PL6 MCB. PL6, 2-pole, tripping characteristic: C, rated current In: 63 A, rated switching capacity IEC/EN 60898-1: 6 kA

### General specifications

|                             |                                      |
|-----------------------------|--------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Moeller series xPole - PL6 MCB |
| <b>CATALOG NUMBER</b>       | 286573                               |
| <b>EAN</b>                  | 4015082865733                        |
| <b>PRODUCT LENGTH/DEPTH</b> | 85 mm                                |
| <b>PRODUCT HEIGHT</b>       | 73 mm                                |
| <b>PRODUCT WIDTH</b>        | 35.4 mm                              |
| <b>PRODUCT WEIGHT</b>       | 0.24 kg                              |
| <b>COMPLIANCES</b>          | RoHS conform                         |
| <b>MODEL CODE</b>           | PL6-C63/2                            |



Powering Business Worldwide

## Delivery program

|                    |   |
|--------------------|---|
| <b>APPLICATION</b> | <ul style="list-style-type: none"><li>• Switchgear for residential and commercial applications</li><li>• xPole - Switchgear for residential and commercial applications</li></ul> |
|--------------------|---|

|                        |          |
|------------------------|----------|
| <b>NUMBER OF POLES</b> | Two-pole |
|------------------------|----------|

|                                |   |
|--------------------------------|---|
| <b>NUMBER OF POLES (TOTAL)</b> | 2 |
|--------------------------------|---|

|                                    |   |
|------------------------------------|---|
| <b>NUMBER OF POLES (PROTECTED)</b> | 2 |
|------------------------------------|---|

|                                |   |
|--------------------------------|---|
| <b>TRIPPING CHARACTERISTIC</b> | C |
|--------------------------------|---|

|                               |   |
|-------------------------------|---|
| <b>RELEASE CHARACTERISTIC</b> | C |
|-------------------------------|---|

|                        |      |
|------------------------|------|
| <b>AMPERAGE RATING</b> | 63 A |
|------------------------|------|

|             |   |
|-------------|---|
| <b>TYPE</b> | <ul style="list-style-type: none"><li>• Miniature circuit breaker</li><li>• PL6</li></ul> |
|-------------|---|

## Technical data - electrical

|                     |    |
|---------------------|----|
| <b>VOLTAGE TYPE</b> | AC |
|---------------------|----|

|   |       |
|---|-------|
| <b>RATED OPERATIONAL VOLTAGE (UE) - MAX</b> | 400 V |
|---|-------|

|                                      |       |
|--------------------------------------|-------|
| <b>RATED INSULATION VOLTAGE (UI)</b> | 440 V |
|--------------------------------------|-------|

|   |      |
|---|------|
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b> | 4 kV |
|---|------|

|                               |       |
|-------------------------------|-------|
| <b>FREQUENCY RATING - MIN</b> | 50 Hz |
|-------------------------------|-------|

|                               |       |
|-------------------------------|-------|
| <b>FREQUENCY RATING - MAX</b> | 60 Hz |
|-------------------------------|-------|

|  |      |
|--|------|
| <b>RATED SWITCHING CAPACITY (IEC/EN 60898-1)</b> | 6 kA |
|--|------|

|  |      |
|--|------|
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 230 V</b> | 6 kA |
|--|------|

|  |      |
|--|------|
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 400 V</b> | 6 kA |
|--|------|

|   |      |
|---|------|
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 230 V</b> | 0 kA |
|---|------|

|   |      |
|---|------|
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 400 V</b> | 0 kA |
|---|------|

|                             |     |
|-----------------------------|-----|
| <b>OVERVOLTAGE CATEGORY</b> | III |
|-----------------------------|-----|

|                         |   |
|-------------------------|---|
| <b>POLLUTION DEGREE</b> | 2 |
|-------------------------|---|

## Technical data - mechanical

|  |                    |
|--|--------------------|
| <b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>                     | 2                  |
| <b>BUILT-IN DEPTH</b>  | 70.5 mm            |
| <b>DEGREE OF PROTECTION</b>                                    | IP20               |
| <b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN</b>  | 1 mm <sup>2</sup>  |
| <b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX</b>  | 25 mm <sup>2</sup> |
| <b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN</b> | 1 mm <sup>2</sup>  |
| <b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX</b> | 25 mm <sup>2</sup> |

## Design verification as per IEC/EN 61439 - technical data

|  |        |
|--|--------|
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 63 A   |
| <b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT</b>                  | 0 W    |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>                 | 11.5 W |
| <b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT</b>                | 0 W    |
| <b>HEAT DISSIPATION CAPACITY</b>                                     | 0 W    |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b>                           | -25 °C |
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>                           | 75 °C  |

## Design verification as per IEC/EN 61439

|   |  |
|---|--|
| <b>10.2.2 CORROSION RESISTANCE</b>  | Meets the product standard's requirements.                         |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.                         |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.                         |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.                         |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | Meets the product standard's requirements.                         |
| <b>10.2.5 LIFTING</b>   | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.2.6 MECHANICAL IMPACT</b>   | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.2.7 INSCRIPTIONS</b>  | Meets the product standard's requirements.                         |
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>  | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>   | Meets the product standard's requirements.                         |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>   | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>                           | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>                                | Is the panel builder's responsibility.                             |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>   | Is the panel builder's responsibility.                             |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>   | Is the panel builder's responsibility.                             |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>   | Is the panel builder's responsibility.                             |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF</b>   | Is the panel builder's responsibility.                             |

## Additional information

|                               |   |
|-------------------------------|---|
| <b>CURRENT LIMITING CLASS</b> | 3   |
| <b>FEATURES</b>               | Additional equipment possible   |
| <b>SPECIAL FEATURES</b>       | Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity |
| <b>USED WITH</b>              | PL6<br>Miniature circuit breaker  |

---

**INSULATING MATERIAL**

---

**10.10 TEMPERATURE RISE**

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

**10.11 SHORT-CIRCUIT RATING**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.12 ELECTROMAGNETIC COMPATIBILITY**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL FUNCTION**

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

---

## Resources

|                                   |   |
|-----------------------------------|---|
|                                   | <a href="#">eaton-miniature-circuit-breaker-xpole-pl6-catalog-ca20190212-en-us.pdf</a>  |
| <b>CATALOGUES</b>                 | <a href="#">eaton-xpole-pl6-mcb-catalog-ca019069en-en-us.pdf</a><br><a href="#">eaton-xpole-protective-devices-catalog-ca019014en-en-us.pdf</a> |
| <b>CHARACTERISTIC CURVE</b>       | <a href="#">eaton-xpole-mmc4-6-mcb-characteristic-curve-002.jpg</a>   |
| <b>DECLARATIONS OF CONFORMITY</b> | <a href="#">DA-DC-03_PL6</a>  |
| <b>DRAWINGS</b>                   | <a href="#">eaton-xpole-pl6-mcb-dimensions.jpg</a><br><a href="#">eaton-xpole-pl6-mcb-3d-drawing-002.jpg</a>                                    |
| <b>INSTALLATION INSTRUCTIONS</b>  | <a href="#">eaton-pdd-rcbo-mcb-installations-il019140zu.pdf</a>   |
| <b>MCAD MODEL</b>                 | <a href="#">pls_2p.dwg pls_2p.stp</a>   |
| <b>WIRING DIAGRAMS</b>            | <a href="#">eaton-xpole-mmc4-6-mcb-wiring-diagram-003.jpg</a>   |

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

