

CAT. N° 0 488 06



LIGHTING MANAGEMENT-DIGITAL PASSAGE DETECTION- CEILING MOUNTING-DT-93 M² AREAS

Pack (number of units)	1
Volume (dm ³)	1,563
Weight (g)	273,00

Product characteristics

For installation in bathrooms

False ceiling detector switch

- Infrared and ultrasonic detection, Ø8 m
- IP 20
- 3-wire with neutral
- Optimum distance between 2 sensors: 6 m
- Standby consumption: 0.8 W
- Fixes directly to a false ceiling with mounting claws (included) or installed in a Batibox box, depth 50 mm
- Connection via automatic terminals
- Can be surface-mounted in ceiling using accessory Cat.No 0 488 75

General characteristics

Lighting to assist with independent living - stand-alone solutions

- Stand-alone automatic lighting devices which allow the patient to get their bearings and make their way to the bathrooms

Documentation

Catalogue pages & additional information

- [Selection chart \(p.659\)](#)
- [Description page \(p.664\)](#)
- [Description page \(p.916\)](#)
- [Motion sensors and Lighting Management sensors for controllers](#)
- [Lighting management stand-alone sensors](#)

Installation instructions & related documents

- [LE02605AF](#)

CAT. N° 0 488 06

 Installation & technical data

- [F01013EN-02](#)

 Video

- [048806_088230_Calibration_01](#)
- [048806_088230_Daylight_01](#)
- [048806_088230_Importexport_01](#)
- [048806_088230_Occupancy_01](#)
- [048806_088230_RegOnOff_01](#)
- [048806_088230_Sensitivity_01](#)
- [048806_088230_Test_01](#)
- [048806_088230_Timedelay_01](#)
- [048806_088230_Vacancy_01](#)
- [048806_088230_Walkthru_01](#)
- [048806_088235_Daylight_01](#)
- [048806_088235_Occupancy_01](#)
- [048806_088235_Sensitivity_01](#)
- [048806_088235_Test_01](#)
- [048806_088235_Timedelay_01](#)
- [048806_088235_Vacancy_01](#)
- [048806_088235_Walkthru_01](#)

 Environmental product profile

- [LGRP-00303-V02](#)

 Documents & videos

- [048806_088230_Calibration_01](#)
- [048806_088230_Daylight_01](#)
- [048806_088230_Importexport_01](#)
- [048806_088230_Occupancy_01](#)
- [048806_088230_RegOnOff_01](#)
- [048806_088230_Sensitivity_01](#)
- [048806_088230_Test_01](#)
- [048806_088230_Timedelay_01](#)
- [048806_088230_Vacancy_01](#)
- [048806_088230_Walkthru_01](#)
- [048806_088235_Daylight_01](#)
- [048806_088235_Occupancy_01](#)
- [048806_088235_Sensitivity_01](#)
- [048806_088235_Test_01](#)
- [048806_088235_Timedelay_01](#)
- [048806_088235_Vacancy_01](#)
- [048806_088235_Walkthru_01](#)

 Agreements & certificates of conformity

- [OC / CB-681064A](#)