

CAT. N° 0 489 33



LIGHTING MANAGEMENT-TRAFFIC DETECTION-CEILING MOUNTING- IR - 270°- RANGE 18 M

Pack (number of units)	1
Volume (dm ³)	1,563
Weight (g)	260,00

Product characteristics

Ideal for outdoor and humid areas

PIR IP 55 wall or ceiling-mounting Lighting Management sensor, 270°

- Multi lens sensor with directional head, range 18 m
- Recommended fixing height: 2.5 m
- 3-wire with neutral
- Standby consumption: 0.7 W
- Can be mounted on an angle using accessory Cat.No 0 489 72

General characteristics

Lighting Management sensors for 1 circuit - Lighting Management sensors for passage areas with natural light

- Check presence and natural light level continuously, switch off when there is sufficient natural light
- Occupancy mode (automatic switch-on/off factory setting)
- Can be used with push-button Cat.No 0 770 40 (or illuminated push-button Cat.No 0 770 33) for vacancy mode (manual switch-on and manual or automatic switch-off)
- Precise on-site adjustment using configuration tool Cat.No 0 882 30
- Adjustable time delay: 5 s to 59 min
- Light level threshold adjustable from 5 to 1275 lux

Documentation

Catalogue pages & additional information

- [Selection chart \(p.659\)](#)
- [Description page \(p.663\)](#)
- [Motion sensors and Lighting Management sensors for controllers](#)
- [Lighting management stand-alone sensors](#)

Installation & technical data

- [S000081482EN-1](#)

Installation instructions & related documents

- [LE06324AA](#)

Environmental product profile

- [LGRP-01574-V01](#)