

CAT. N° 0 488 22



## LIGHTING MANAGEMENT--WALL MOUNTING-DT-360°-FOR 93 M<sup>2</sup> AREAS - FLUSH MOUNTING

|                           |        |
|---------------------------|--------|
| Pack (number of units)    | 1      |
| Volume (dm <sup>3</sup> ) | 1,563  |
| Weight (g)                | 235,00 |

### Product characteristics

#### Ideal for working areas

#### Dual technology ceiling-mounting Lighting Management sensor, 360°

- Infrared and ultrasonic detection, range Ø8 m
- Recommended fixing height: 2.50 m
- IP 20
- Optimum distance between 2 sensors: 6 m
- Consumption: 0.5 W on standby
- Fixes directly to a false ceiling with mounting claws (included) or installed in a Batibox box, depth 50 mm
- Can be surface-mounted on ceiling using accessory Cat. No 0 488 75

### General characteristics

#### Lighting Management sensors for managing several circuits - Lighting Management sensors for controllers for passage areas and working areas with natural light

- Check presence and light level continuously, switch off when there is sufficient natural light
- Automatic switch-on/off (factory setting)
- Precise on-site adjustment using configuration tool
- Connect to controllers by cord or RJ 45 cable or BUS/SCS cable to be fitted with RJ 45 connector Cat.No 0 488 72

### Documentation

#### Catalogue pages & additional information

- [Description page \(p.426\)](#)
- [Selection chart \(p.660\)](#)
- [Description page \(p.666\)](#)
- [Motion sensors and Lighting Management sensors for controllers](#)
- [Lighting management stand-alone sensors](#)

#### Installation & technical data

- [F01127EN-02](#)

#### Installation instructions & related documents

- [LE02817AD](#)

#### Environmental product profile

- [LGRP-00069-V01](#)