

CAT. N° 3 101 54



ON-LINE DOUBLE CONVERSION UPS - TOWER - 1000 VA - 900 W

Pack (number of units)	1
Volume (dm ³)	63,763
Weight (g)	11 794,00

Product characteristics

UPS with IEC sockets

- The stated backup time in minutes is estimated and may vary according to the load characteristics, operating conditions and environment
- Nominal power: : 1000 VA
- Active power: : 900 W
- Backup time: : 5 min
- No. of sockets IEC (10 A): : 3
- Weight: : 10 kg

General characteristics

Keor LP - On-line double conversion UPS (tower) - single phase VFI

- For security systems, lighting systems, CCTV, servers. Ideal for environments with frequent electrical disturbances
- Installation: downstream power generators. Advanced management depending on the battery discharge level
- Self-diagnosis. Power factor: 0.9
- Automatic internal bypass, manual bypass for external maintenance (optional)
- Integrated slot for installing a communication interface for Ethernet network connection, to be ordered separately
- Cold Start function
- Microprocessor control
- Telephone line/Internet protection (RJ 11/RJ 45)
- Internal network interface Cat.No 3 108 82 for remote protection of equipment and systems
- Remote emergency shutdown function ("Emergency Power Off" - EPO)

Documentation

Catalogue pages & additional information

- [Description page \(p.704\)](#)

Installation & technical data

- [UPS_LGR_0086_GB_AA](#)

Installation instructions & related documents

- [LE07360AC](#)

Environmental product profile

- [LGRP-2015-278-V1-EN](#)