

CAT. N° 3 109 60



ADDITIONAL BATTERY CHARGER - FOR BATTERY CABINET CAT.NO 3 105 99

| | |
|---------------------------|----------|
| Pack (number of units) | 1 |
| Volume (dm ³) | 11,977 |
| Weight (g) | 2 465,00 |

Product characteristics

Additional battery cabinets

Additional battery chargers

- For battery cabinet Cat.No 3 105 99

General characteristics

Keor LP - On-line double conversion UPS (tower) - single phase VFI

- For security systems, lighting systems, CCTV, servers. Ideal for environments with frequent electrical disturbances
- Installation: downstream power generators. Advanced management depending on the battery discharge level
- Self-diagnosis. Power factor: 0.9
- Automatic internal bypass, manual bypass for external maintenance (optional)
- Integrated slot for installing a communication interface for Ethernet network connection, to be ordered separately
- Cold Start function
- Microprocessor control
- Telephone line/Internet protection (RJ 11/RJ 45)
- Internal network interface Cat.No 3 108 82 for remote protection of equipment and systems
- Remote emergency shutdown function ("Emergency Power Off" - EPO)

Documentation



Catalogue pages & additional information

- [Description page \(p.704\)](#)



Installation instructions & related documents

- [LE09122AA](#)