

CAT. N° 3 109 61



ADDITIONAL BATTERY CHARGER - FOR BATTERY CABINET CAT.NO 3 106 00

Pack (number of units)	1
Volume (dm ³)	11,977
Weight (g)	2 400,00

Product characteristics

Accessories

- For battery cabinet Cat.No 3 106 00

General characteristics

DAKER DK PLUS - On-line double conversion UPS (rack/tower) - single phase and three phase VFI

- The main parameters of the UPS, including the battery charge level and faults, are displayed on the LCD screen on the front panel
- The integrated communication software not only controls the UPS and its switch-off if there is a malfunction, and enables the user to test the main functions remotely, communicate via SNMP/Internet/network adaptor and access the functions of the UPS via the Internet, but can also send the user an SMS if specific events occur
- The internal extension connector enables aWEB/SNMP card or a relay interface to be installed which provides insulated contacts for applications on industrial control panels or remote alarm panels
- If there is an electronic fault, overload, overheating or for scheduled maintenance operations, the automatic or manual (optional) bypass ensures continuity of the power supply for critical loads. A bypass switch is available for maintenance

Documentation



Catalogue pages & additional information

- [Description page \(p.704\)](#)
- [Description page \(p.705\)](#)
- [Technical page \(p.706\)](#)
- [Description page \(p.707\)](#)
- [Technical page \(p.708\)](#)
- [DAKER DK PLUS](#)



Installation instructions & related documents

- [LE09122AA](#)